



Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024

Version number 1.2

Revision: 05.07.2024

1 Identification

- **Product identifier**
- **Trade name:** 5000M 2K CLEAR SATIN GLOSS
- **Article number:** 5000M
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Sector of Use**
SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category**
PC9a Coatings and paints, thinners, paint removers
PC9b Fillers, putties, plasters, modelling clay
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Manufacturer:
General Paint Company S.A.L.
P.O.Box 7623
Beirut, Lebanon
info@generalpaint.biz
www.generalpaint.biz
Importer:
Payless Services Pty. Ltd.
A Pacific Express Group Company
103 Eldridge Road
Bankstown, NSW, 2200
Australia
- **Further information obtainable from:** Product Safety Department
- **Emergency telephone number:**
Phone : +61 297085698
Mobile: +61 413703038

2 Hazard(s) Identification

- **Classification of the substance or mixture**



GHS02 flame

Flammable liquids – Category 2

H225 Highly flammable liquid and vapour.



GHS08 health hazard

(Contd. on page 2)



Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024

Version number 1.2

Revision: 05.07.2024

Trade name: 5000M 2K CLEAR SATIN GLOSS

(Contd. of page 1)

*Reproductive toxicity – Category 1A**H360 May damage fertility or the unborn child.**Specific target organ toxicity (repeated exposure) – Category 2**H373 May cause damage to the hearing organs through prolonged or repeated exposure.**Aspiration hazard – Category 1**H304 May be fatal if swallowed and enters airways.*

GHS07

*Skin corrosion/irritation – Category 2**H315 Causes skin irritation.**Specific target organ toxicity (single exposure) – Category 3**H336 May cause drowsiness or dizziness.***Label elements****GHS label elements***The product is classified and labelled according to the Globally Harmonised System (GHS).***Hazard pictograms**

GHS02 GHS07 GHS08

Signal word Danger**Hazard-determining components of labelling:***toluene (>10-≤25 %)**n-butyl acetate (>25-≤50 %)**ethylbenzene (≤2.5 %)***Hazard statements***Highly flammable liquid and vapour.**Causes skin irritation.**May damage fertility or the unborn child.**May cause drowsiness or dizziness.**May cause damage to the hearing organs through prolonged or repeated exposure.**May be fatal if swallowed and enters airways.***Precautionary statements***If medical advice is needed, have product container or label at hand.**Keep out of reach of children.**Read label before use.**IF SWALLOWED: Immediately call a POISON CENTER/ doctor.**Specific treatment (see on this label).**Do NOT induce vomiting.*

(Contd. on page 3)



Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024

Version number 1.2

Revision: 05.07.2024

Trade name: 5000M 2K CLEAR SATIN GLOSS

(Contd. of page 2)

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition and Information on Ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

123-86-4	<i>n</i> -butyl acetate	>25-≤50%
108-88-3	toluene	>10-≤25%
1330-20-7	xylene	>2.5-≤10%
112926-00-8	Precipitated silica (Silica-Amorphous)	>2.5-≤10%
108-65-6	2-methoxy-1-methylethyl acetate	≤2.5%
78-93-3	butanone	≤2.5%
100-41-4	ethylbenzene	≤2.5%
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	≤2.5%
104810-47-1	<i>s</i> -3-(3-(2 <i>h</i> -benzotriazol-2-yl)-5- <i>t</i> -butyl-4-hydroxyphenyl)propionol- ohydroxypoly(oxyethylene); <i>a</i> -3-(3-(2 <i>h</i> -	≤2.5%
80-62-6	methyl methacrylate	≤2.5%
26761-45-5	2,3-epoxypropyl neodecanoate	≤2.5%
82919-37-7	methyl 1,2,2,6,6,6-pentamethyl-4-piperidyl sebacate	≤2.5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.

(Contd. on page 4)

AU



Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024

Version number 1.2

Revision: 05.07.2024

Trade name: 5000M 2K CLEAR SATIN GLOSS

(Contd. of page 3)

- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire Fighting Measures

- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and Storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.

(Contd. on page 5)



Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024

Version number 1.2

Revision: 05.07.2024

Trade name: 5000M 2K CLEAR SATIN GLOSS

(Contd. of page 4)

- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.

· **Ingredients with limit values that require monitoring at the workplace:**

123-86-4 n-butyl acetate

WES Short-term value: 950 mg/m³, 200 ppm
Long-term value: 713 mg/m³, 150 ppm

108-88-3 toluene

WES Short-term value: 574 mg/m³, 150 ppm
Long-term value: 191 mg/m³, 50 ppm
Sk

1330-20-7 xylene

WES Short-term value: 655 mg/m³, 150 ppm
Long-term value: 350 mg/m³, 80 ppm

112926-00-8 Precipitated silica (Silica-Amorphous)

WES Long-term value: 10 mg/m³
inhalable dust

108-65-6 2-methoxy-1-methylethyl acetate

WES Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

78-93-3 butanone

WES Short-term value: 890 mg/m³, 300 ppm
Long-term value: 445 mg/m³, 150 ppm

(Contd. on page 6)

-AU-



Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024

Version number 1.2

Revision: 05.07.2024

Trade name: 5000M 2K CLEAR SATIN GLOSS

(Contd. of page 5)

100-41-4 ethylbenzene

WES	Short-term value: 543 mg/m ³ , 125 ppm Long-term value: 434 mg/m ³ , 100 ppm
-----	---

80-62-6 methyl methacrylate

WES	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm Sen
-----	---

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing
 - Wash hands before breaks and at the end of work.
 - Store protective clothing separately.
 - Avoid contact with the skin.
 - Avoid contact with the eyes and skin.
- **Respiratory protection:**
 - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 - The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

AU



Safety Data Sheet

according to WHS Regulations

Printing date 05.07.2024

Version number 1.2

Revision: 05.07.2024

Trade name: 5000M 2K CLEAR SATIN GLOSS

(Contd. of page 6)

· Eye protection:

Tightly sealed goggles

9 Physical and Chemical Properties

· General Information**· Appearance:**

- **Form:** Liquid
- **Colour:** Clear
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **pH-value:** Not determined.

· Change in condition

- **Melting point/freezing point:** Undetermined.

- **Initial boiling point and boiling range:** 110 °C

- **Flash point:** 4 °C
- **Flammability (solid, gas):** Highly flammable.

- **Auto-ignition temperature:** 370 °C

- **Decomposition temperature:** Not determined.

- **Ignition temperature:** Product is not selfigniting.

- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

- **Lower:** 1.2 Vol %

- **Upper:** 7.5 Vol %

- **Vapour pressure at 20 °C:** 29 hPa

- **Density at 20 °C:** 0.991 g/cm³

- **Relative density** Not determined.

- **Vapour density** Not determined.

- **Evaporation rate** Not determined.

· Solubility in / Miscibility with

- **water:** Not miscible or difficult to mix.

- **Partition coefficient: n-octanol/water:** Not determined.

· Viscosity:

- **Dynamic:** Not determined.

- **Kinematic:** Not determined.

· Solvent content:

- **Organic solvents:** 53.6 %

- **VOC (EC)** 531.1 g/l

(Contd. on page 8)

AU



Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024

Version number 1.2

Revision: 05.07.2024

Trade name: 5000M 2K CLEAR SATIN GLOSS

(Contd. of page 7)

- | | |
|----------------------------|--|
| · Solids content: | 45.2 % |
| · Other information | No further relevant information available. |

10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:**123-86-4 n-butyl acetate**

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** May damage fertility or the unborn child.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure**
May cause damage to the hearing organs through prolonged or repeated exposure.
- **Aspiration hazard** May be fatal if swallowed and enters airways.

12 Ecological Information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 9)



Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024

Version number 1.2

Revision: 05.07.2024

Trade name: 5000M 2K CLEAR SATIN GLOSS


(Contd. of page 8)

- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|-----------------------------|
| · UN-Number | |
| · ADG, IMDG, IATA | UN1263 |
| · UN proper shipping name | |
| · ADG | 1263 PAINT RELATED MATERIAL |
| · IMDG, IATA | PAINT RELATED MATERIAL |
| · Transport hazard class(es) | |
| · ADG, IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids. |
| · Label | 3 |
| · Packing group | |
| · ADG | Void |

(Contd. on page 10)



Safety Data Sheet

according to WHS Regulations

Printing date 05.07.2024

Version number 1.2

Revision: 05.07.2024

Trade name: 5000M 2K CLEAR SATIN GLOSS

(Contd. of page 9)

· IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids.
· EMS Number:	F-E,S-C
· Stowage Category	B
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	

· ADG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E

· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Australian Inventory of Industrial Chemicals**

123-86-4	n-butyl acetate
108-88-3	toluene
1330-20-7	xylene
112926-00-8	Precipitated silica (Silica-Amorphous)
108-65-6	2-methoxy-1-methylethyl acetate
78-93-3	butanone
100-41-4	ethylbenzene
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

(Contd. on page 11)

AU



Safety Data Sheet

according to WHS Regulations

Printing date 05.07.2024

Version number 1.2

Revision: 05.07.2024

Trade name: 5000M 2K CLEAR SATIN GLOSS

(Contd. of page 10)

104810-47-1	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol- ohydroxypoly(oxyethylene);a-3-(3-(2h-
80-62-6	methyl methacrylate
26761-45-5	2,3-epoxypropyl neodecanoate
82919-37-7	methyl 1,2,2,6,6,6-pentamethyl-4-piperidyl sebacate
79-41-4	methacrylic acid
868-77-9	2-hydroxyethyl methacrylate
141-32-2	n-butyl acrylate
78-83-1	butanol
103-11-7	2-ethylhexyl acrylate
77-58-7	dibutyltin dilaurate
556-67-2	octamethylcyclotetrasiloxane

• **Standard for the Uniform Scheduling of Medicines and Poisons**

108-88-3	toluene	S6
1330-20-7	xylene	S6
78-93-3	butanone	S5
80-62-6	methyl methacrylate	S6, S10
868-77-9	2-hydroxyethyl methacrylate	S5

• **Australia: Priority Existing Chemicals**

None of the ingredients is listed.

• **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

• **Hazard pictograms**



GHS02 GHS07 GHS08

• **Signal word** Danger

• **Hazard-determining components of labelling:**

toluene (>10-≤25 %)
n-butyl acetate (>25-≤50 %)
ethylbenzene (≤2.5 %)

• **Hazard statements**

Highly flammable liquid and vapour.
Causes skin irritation.
May damage fertility or the unborn child.
May cause drowsiness or dizziness.

(Contd. on page 12)

-AU-



Safety Data Sheet according to WHS Regulations

Printing date 05.07.2024

Version number 1.2

Revision: 05.07.2024

Trade name: 5000M 2K CLEAR SATIN GLOSS

(Contd. of page 11)

May cause damage to the hearing organs through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.

Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Directive 2012/18/EU

• **Named dangerous substances - ANNEX I** None of the ingredients is listed.

• **Seveso category** P5c FLAMMABLE LIQUIDS

• **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

• **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Department issuing SDS:** Product safety department

• **Contact:** N/A

Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flammable liquids – Category 2: Flammable liquids – Category 2

Skin corrosion/irritation – Category 2: Skin corrosion/irritation – Category 2

Reproductive toxicity – Category 1A: Reproductive toxicity – Category 1A

Specific target organ toxicity (single exposure) – Category 3: Specific target organ toxicity (single exposure) – Category 3

Specific target organ toxicity (repeated exposure) – Category 2: Specific target organ toxicity (repeated exposure) – Category 2

Aspiration hazard – Category 1: Aspiration hazard – Category 1

• *** Data compared to the previous version altered.**