



## Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

### 1 Identification

- **Product identifier**
- **Trade name:** H750 2K HARDENER EXTRA SLOW
- **Article number:** H750
- **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.  
none
- **Sector of Use**  
SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites  
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category**  
PC9a Coatings and paints, thinners, paint removers  
PC9b Fillers, putties, plasters, modelling clay
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Manufacturer:  
General Paint Company S.A.L.  
P.O.Box 7623  
Beirut, Lebanon  
info@generalpaint.biz  
www.generalpaint.biz  
Importer:  
Payless Services Pty. Ltd.  
A Pacific Express Group Company  
103 Eldridge Road  
Bankstown, NSW, 2200  
Australia
- **Further information obtainable from:** Product Safety Department
- **Emergency telephone number:**  
Phone : +61 297085698  
Mobile: +61 413703038

### 2 Hazard(s) Identification

- **Classification of the substance or mixture**



GHS02 flame

Flammable liquids – Category 3

H226 Flammable liquid and vapour.

(Contd. on page 2)



## Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

**Trade name: H750 2K HARDENER EXTRA SLOW**

(Contd. of page 1)



GHS07

*Acute toxicity - dermal – Category 4**Skin corrosion/irritation – Category 2**Eye damage/irritation – Category 2A**Specific target organ toxicity (single exposure) – Category 3**H312 Harmful in contact with skin.**H315 Causes skin irritation.**H319 Causes serious eye irritation.**H335 May cause respiratory irritation.***Label elements****GHS label elements***The product is classified and labelled according to the Globally Harmonised System (GHS).***Hazard pictograms**

GHS02 GHS07

**Signal word** Warning**Hazard-determining components of labelling:***Homopolymer of hexamethylene diisocyanate (>25-≤50 %)**xylene (>10-≤25 %)**2-butoxyethyl acetate (>2.5-≤10 %)***Hazard statements***Flammable liquid and vapour.**Harmful in contact with skin.**Causes skin irritation.**Causes serious eye irritation.**May cause respiratory irritation.***Precautionary statements***If medical advice is needed, have product container or label at hand.**Keep out of reach of children.**Read label before use.**Keep away from heat/sparks/open flames/hot surfaces. No smoking.**Use explosion-proof electrical/ventilating/lighting equipment.**IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 3)



## Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

**Trade name: H750 2K HARDENER EXTRA SLOW**

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition and Information on Ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

28182-81-2	Homopolymer of hexamethylene diisocyanate	>25-≤50%
108-65-6	2-methoxy-1-methylethyl acetate	>10-≤25%
64742-95-6	Solvent naphtha (petroleum), light arom.	>10-≤25%
1330-20-7	xylene	>10-≤25%
112-07-2	2-butoxyethyl acetate	>2.5-≤10%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### 4 First Aid Measures

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Fire Fighting Measures

- **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)



## Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

**Trade name: H750 2K HARDENER EXTRA SLOW**

(Contd. of page 3)

- **Protective equipment:** No special measures required.

### 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and Storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.
- **Ingredients with limit values that require monitoring at the workplace:**

**108-65-6 2-methoxy-1-methylethyl acetate**

WES	Short-term value: 548 mg/m <sup>3</sup> , 100 ppm
	Long-term value: 274 mg/m <sup>3</sup> , 50 ppm
Sk	

(Contd. on page 5)



## Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

**Trade name: H750 2K HARDENER EXTRA SLOW**

(Contd. of page 4)

**1330-20-7 xylene**

WES Short-term value: 655 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 350 mg/m<sup>3</sup>, 80 ppm

**112-07-2 2-butoxyethyl acetate**

WES Short-term value: 333 mg/m<sup>3</sup>, 50 ppm  
Long-term value: 133 mg/m<sup>3</sup>, 20 ppm  
Sk

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Respiratory protection:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

AU



## Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

**Trade name: H750 2K HARDENER EXTRA SLOW**

(Contd. of page 5)

**· Eye protection:**

Tightly sealed goggles

### 9 Physical and Chemical Properties

**· General Information****· Appearance:**

- **Form:** Liquid
- **Colour:** Clear
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **pH-value:** Not determined.

**· Change in condition**

- **Melting point/freezing point:** Undetermined.
- **Initial boiling point and boiling range:** 137 °C
- **Flash point:** 25 °C
- **Flammability (solid, gas):** Flammable.
- **Auto-ignition temperature:** 315 °C
- **Decomposition temperature:** Not determined.
- **Ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

**· Explosion limits:**

- **Lower:** 0.7 Vol %
- **Upper:** 10.8 Vol %
- **Vapour pressure at 20 °C:** 6.7 hPa
- **Density at 20 °C:** 1.005 g/cm<sup>3</sup>
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with**
- **water:** Not miscible or difficult to mix.
- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity:**
- **Dynamic:** Not determined.
- **Kinematic:** Not determined.
- **Solvent content:**
- **Organic solvents:** 52.2 %
- **VOC (EC)** 524.5 g/l

(Contd. on page 7)

-AU-



## Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

**Trade name: H750 2K HARDENER EXTRA SLOW**

(Contd. of page 6)

- |                            |  |
|----------------------------|--|
| · <b>Solids content:</b>   | 47.7 %                                     |
| · <b>Other information</b> | No further relevant information available. |

### 10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity** Harmful in contact with skin.
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### 12 Ecological Information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 8)

-AU



## Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

**Trade name: H750 2K HARDENER EXTRA SLOW**


(Contd. of page 7)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |   |                             |
|---|-----------------------------|
| · <b>UN-Number</b>  |                             |
| · <b>ADG, IMDG, IATA</b>  | UN1263                      |
| · <b>UN proper shipping name</b>  |                             |
| · <b>ADG</b>  | 1263 PAINT                  |
| · <b>IMDG, IATA</b>   | PAINT                       |
| · <b>Transport hazard class(es)</b>   |                             |
| · <b>ADG, IMDG, IATA</b>  |                             |
|  |                             |
| · <b>Class</b>  | 3 Flammable liquids.        |
| · <b>Label</b>  | 3                           |
| · <b>Packing group</b>  |                             |
| · <b>ADG, IMDG, IATA</b>  | III                         |
| · <b>Environmental hazards:</b>   |                             |
| · <b>Marine pollutant:</b>  | No                          |
| · <b>Special precautions for user</b>   | Warning: Flammable liquids. |
| · <b>Hazard identification number (Kemler code):</b>                                | 30                          |
| · <b>EMS Number:</b>  | F-E,S-E                     |
| · <b>Stowage Category</b>   | A                           |

(Contd. on page 9)

AU





## Safety Data Sheet

according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

**Trade name: H750 2K HARDENER EXTRA SLOW**

(Contd. of page 8)

- |   |  |
|---|--|
| <b>· Transport in bulk according to Annex II of Marpol and the IBC Code</b> | Not applicable.  |
| <b>· Transport/Additional information:</b>                                  |  |
| <b>· ADG</b>  |  |
| · Limited quantities (LQ)   | 5L   |
| · Excepted quantities (EQ)  | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| <b>· Transport category</b>   |  |
| · Tunnel restriction code   | 3<br>D/E   |
| <b>· IMDG</b>   |  |
| · Limited quantities (LQ)   | 5L   |
| · Excepted quantities (EQ)  | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| <b>· UN "Model Regulation":</b>   | UN 1263 PAINT, 3, III  |

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture

- **Australian Inventory of Industrial Chemicals**

28182-81-2	Homopolymer of hexamethylene diisocyanate
108-65-6	2-methoxy-1-methylethyl acetate
1330-20-7	xylene
112-07-2	2-butoxyethyl acetate
822-06-0	hexamethylene-di-isocyanate
4083-64-1	4-isocyanatosulphonyltoluene

- **Standard for the Uniform Scheduling of Medicines and Poisons**

1330-20-7	xylene	S6
-----------	--------	----

- **Australia: Priority Existing Chemicals**

None of the ingredients is listed.

- **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

(Contd. on page 10)

AU



## Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

**Trade name: H750 2K HARDENER EXTRA SLOW**

(Contd. of page 9)

**· Hazard pictograms**

GHS02 GHS07

**· Signal word** Warning**· Hazard-determining components of labelling:**

Homopolymer of hexamethylene diisocyanate (&gt;25-≤50 %)

xylene (&gt;10-≤25 %)

2-butoxyethyl acetate (&gt;2.5-≤10 %)

**· Hazard statements**

Flammable liquid and vapour.

Harmful in contact with skin.

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

**· Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Directive 2012/18/EU****· Named dangerous substances - ANNEX I** None of the ingredients is listed.**· Seveso category** P5c FLAMMABLE LIQUIDS**· Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t**· Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Department issuing SDS:** Product safety department

(Contd. on page 11)

-AU-



## Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

**Trade name: H750 2K HARDENER EXTRA SLOW**

(Contd. of page 10)

• **Contact:** N/A

• **Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organisation*

*ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*VOC: Volatile Organic Compounds (USA, EU)*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*Flammable liquids – Category 3: Flammable liquids – Category 3*

*Acute toxicity - dermal – Category 4: Acute toxicity – Category 4*

*Skin corrosion/irritation – Category 2: Skin corrosion/irritation – Category 2*

*Eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A*

*Specific target organ toxicity (single exposure) – Category 3: Specific target organ toxicity (single exposure) – Category 3*

• **\* Data compared to the previous version altered.**

AU