

Page 1/11

Safety Data Sheet

according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

1 Identification · Product identifier · Trade name: H760 2K HARDENER SPECIAL · Article number: H760 · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. none · Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) · Product category PC9a Coatings and paints, thinners, paint removers PC9b Fillers, putties, plasters, modelling clay · Details of the supplier of the safety data sheet Manufacturer/Supplier: Manufacturer: General Paint Company S.A.L. P.O.Box 7623 Beirut, Lebanon info@generalpaint.biz www.generalpaint.biz Importer: Payless Services Pty. Ltd. A Pacific Express Group Company 103 Eldridge Road Bankstown, NSW, 2200 Australia · Further information obtainable from: Product Safety Department · Emergency telephone number: Phone : +61 297085698 Mobile: +61 413703038

· Classification of the substance or mixture



Flammable liquids – Category 3

H226 Flammable liquid and vapour.

(Contd. on page 2)



Page 2/11

Safety Data Sheet

according to WHS Regulations Version number 1.1

Revision: 06.07.2024

Trade name: H760 2K HARDENER SPECIAL

Printing date 06.07.2024

(Contd. of page 1) GHS07 Acute toxicity - dermal – Category 4 H312 Harmful in contact with skin. Skin corrosion/irritation – Category 2 H315 Causes skin irritation. Eye damage/irritation – Category 2A H319 Causes serious eye irritation. Specific target organ toxicity (single exposure) -H335 May cause respiratory irritation. Category 3 · Label elements · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS). Hazard pictograms GHS02 GHS07 · Signal word Warning · Hazard-determining components of labelling: Homopolymer of hexamethylene diisocyanate (>25-≤50 %) 2-butoxyethyl acetate (>2.5-≤10 %) xylene (>2.5-≤10 %) · Hazard statements Flammable liquid and vapour. Harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use explosion-proof electrical/ventilating/lighting equipment. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 3)



Page 3/11

Safety Data Sheet

according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

(Contd. of page 2)

Trade name: H760 2K HARDENER SPECIAL

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition and Information on Ingredients

· Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

28182-81-2	Homopolymer of hexamethylene diisocyanate	>25- <i>≤</i> 50%
108-65-6	2-methoxy-1-methylethyl acetate	>10- <i>≤</i> 25%
64742-95-6	Solvent naphtha (petroleum), light arom.	>10- <i>≤</i> 25%
112-07-2	2-butoxyethyl acetate	>2.5- <i>≤</i> 10%
1330-20-7	xylene	>2.5- <i>≤</i> 10%
Additional information. For the wording of the listed beyond phrases refer to eastion 16		

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)



Safety Data Sheet

according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: H760 2K HARDENER SPECIAL

· Protective equipment: No special measures required.

(Contd. of page 3)

Page 4/11

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
 Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and Storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see section 7.

· Ingredients with limit values that require monitoring at the workplace:

108-65-6 2-methoxy-1-methylethyl acetate

WES Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

(Contd. on page 5)

AU



Page 5/11

Safety Data Sheet

according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

(Contd. of page 4)

Trade name: H760 2K HARDENER SPECIAL

112-07-2 2-butoxyethyl acetate

WES Short-term value: 333 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm Sk

1330-20-7 xylene

WES Short-term value: 655 mg/m³, 150 ppm Long-term value: 350 mg/m³, 80 ppm

· Additional information: The lists valid during the making were used as basis.

· Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

AU



Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: H760 2K HARDENER SPECIAL

· Eye protection:



Tightly sealed goggles

9 Physical and Chemical Properties

· General Information	
· Appearance:	
Form:	Liquid
· Colour:	Clear
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
 Change in condition 	
 Melting point/freezing point: 	Undetermined.
 Initial boiling point and boiling range: 	137 °C
· Flash point:	25 °C
 Flammability (solid, gas): 	Flammable.
 Auto-ignition temperature: 	280 °C
 Decomposition temperature: 	Not determined.
 Ignition temperature: 	Product is not selfigniting.
 Explosive properties: 	Product is not explosive. However, formation of explosive air/
	vapour mixtures are possible.
 Explosion limits: 	
· Lower:	0.7 Vol %
· Upper:	10.8 Vol %
 Vapour pressure at 20 °C: 	5 hPa
· Density at 20 °C:	1.01 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
 Solubility in / Miscibility with 	
· water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
· Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	50 0 0/
· Organic solvents:	52.3 %
· VOC (EC)	527.8 g/l
	(Contd. on page 7)

Page 6/11

(Contd. of page 5)

AU



Page 7/11

Safety Data Sheet

according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

(Contd. of page 6)

Trade name: H760 2K HARDENER SPECIAL

· Solids content:

47.6 %

· Other information

No further relevant information available.

10 Stability and Reactivity

· Reactivity No further relevant information available.

- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- \cdot Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity Harmful in contact with skin.
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause respiratory irritation.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological Information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 8)

AU



Page 8/11

Safety Data Sheet

according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

(Contd. of page 7)

Trade name: H760 2K HARDENER SPECIAL

· Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
ADG, IMDG, IATA	UN1263	
UN proper shipping name		
ADG	1263 PAINT	
IMDG, IATA	PAINT	
Transport hazard class(es)		
ADG, IMDG, IATA		
Class	3 Flammable liquids.	
Label	3	
Packing group		
ADG, IMDG, IATA	<i>III</i>	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids.	
Hazard identification number (Kemle		
EMS Number:	F-E, <u>S-E</u>	



Page 9/11

Safety Data Sheet

according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: H760 2K HARDENER SPECIAL

	(Contd. of page
 Transport in bulk according to Annex II of Marpol and the IBC Code 	Not applicable.
· Transport/Additional information:	
 ADG Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 D/E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Industrial Chemicals

- 28182-81-2 Homopolymer of hexamethylene diisocyanate
- 108-65-6 2-methoxy-1-methylethyl acetate
- 112-07-2 2-butoxyethyl acetate
- 1330-20-7 xylene
 - 822-06-0 hexamethylene-di-isocyanate

4083-64-1 4-isocyanatosulphonyltoluene

- · Standard for the Uniform Scheduling of Medicines and Poisons
- 1330-20-7 xylene

· Australia: Priority Existing Chemicals

None of the ingredients is listed.

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

(Contd. on page 10)

S6



Page 10/11

Safety Data Sheet

according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: H760 2K HARDENER SPECIAL

(Contd. of page 9) Hazard pictograms GHS02 GHS07 · Signal word Warning · Hazard-determining components of labelling: Homopolymer of hexamethylene diisocyanate (>25-≤50 %) 2-butoxyethyl acetate (>2.5-≤10 %) xylene (>2.5-≤10 %) · Hazard statements Flammable liquid and vapour. Harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use explosion-proof electrical/ventilating/lighting equipment. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Directive 2012/18/EU · Named dangerous substances - ANNEX I None of the ingredients is listed. · Seveso category P5c FLAMMABLE LIQUIDS • Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t • Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t · Chemical safety assessment: A Chemical Safety Assessment has not been carried out. 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

(Contd. on page 11)

- AU



Page 11/11

Safety Data Sheet according to WHS Regulations

Printing date 06.07.2024

Version number 1.1

Revision: 06.07.2024

Trade name: H760 2K HARDENER SPECIAL

	(Contd. of page
Contact: N/A	
Abbreviation	is and acronyms:
	international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concern Transport of Dangerous Goods by Rail)
ICAO: Internation	nal Civil Aviation Örganisation
International Car	atif au transport international des marchandises dangereuses par route (European Agreement Concerning riage of Dangerous Goods by Road)
	nal Maritime Code for Dangerous Goods
IATA: Internation	al Air Transport Association
EINECS: Europe	an Inventory of Existing Commercial Chemical Substances
ELINCS: Europe	an List of Notified Chemical Substances
CAS: Chemical A	Abstracts Service (division of the American Chemical Society)
VOC: Volatile Or	ganic Compounds (USA, EU)
PBT: Persistent,	Bioaccumulative and Toxic
vPvB: very Persi	stent and very Bioaccumulative
Flammable liquid	ls – Category 3: Flammable liquids – Category 3
Acute toxicity - d	ermal – Čategory 4: Acute toxicity – Category 4
Skin corrosion/ir	itation – Category 2: Skin corrosion/irritation – Category 2
	ation – Category 2A: Serious eye damage/eye irritation – Category 2A
	gan toxicity (single exposure) – Category 3: Specific target organ toxicity (single exposure) – Category 3
	ared to the previous version altered.
Data Comp	