



# G806 – Easy Polyester Putty Grey

## Product Description

This great metal filler is a multi-purpose putty with an extremely smooth application. It can be applied vertically without running and exhibits high resistance to almost all solvents. It is characterized by very easy sanding and the advantage of withstanding temperatures of 100°C without any distortions.

## Suitable Substrates:

- Iron, steel plate, glass fiber reinforced plastic
- Original paints or aged topcoat finishes

## Surface Preparation:

- Clean well the surface to be treated with 8241 Genclean. Make sure it is dry and free from
- Silicone, wax, grease and any extraneous material.
- On basecoats or enamel top coats, sand and clean the surface before applying the filler..

## Product Application



1 – 3% General hardener  
Potlife 3-5 min at 20°C



Application with putty knife



< 30 min at 20°C



4 – 5 min at 1 m.

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.



# G80G – Easy Polyester Putty Grey



Initial Sanding with P60 – P120 roughing-out  
Final Sanding with P180 – P220 finishing

## Product Characteristics

<b>VOC(2004/42/EC):</b>	2004/42/II B (b) (250)250. The EU limit value for this product (product category II B.b) in ready to use form is max 250g/ltr. The VOC content of this product in ready for use form is max. 250 g/l.
<b>Composition</b>	Unsaturated polyester resin and mineral charges
<b>Specific Weight:</b>	1.83 ± 0.1
<b>Available Colors:</b>	Beige, Grey
<b>SDS:</b>	Refer to the Safety Data Sheet.

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.