

Page 1/12

Safety data sheet

according to 1907/2006/EC, Article 31) with its amendment Regulation (EU) 2020/878

Printing date 17.05.2024

Version number 1.1

Revision: 17.05.2024

SECTION 1: Identification of the substance/mixture and of the company, undertaking

- · 1.1 Product identifier
- · Trade name: 5500 AIR BAKE SR CLEAR
- · Article number: 5500
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available. use as industrial paint
- · Sector of Use

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- Product category
 PC9a Coatings and paints, thinners, paint removers
 PC9b Fillers, putties, plasters, modelling clay
 Application of the substance / the mixture refer to the relevant Technical Data Sheet
- Application of the substance, the mixture fold to the foldwart foormean
- 1.3 Details of the supplier of the safety data sheet

 Manufacturer/Supplier: Générale de Peinture,
 70 Rue Cortambert 75116 Paris, France Tel:+33(0)175293559 info@generalpaint.biz

- · Further information obtainable from: Product Safety Department
- · 1.4 Emergency telephone number: Phone : :+33 (0)6 07 87 13 41

SECTION 2: Hazards identification

 2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008) with its amendment Regulation (EU) 2020/878



Flam. Liq. 3 H226 Flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

GB



Safety data sheet

according to 1907/2006/EC, Article 31) with its amendment Regulation (EU) 2020/878


Printing date 17.05.2024

Version number 1.1

Revision: 17.05.2024

Page 2/12

Trade name: 5500 AIR BAKE SR CLEAR



- GB



Page 3/12

Safety data sheet according to 1907/2006/EC, Article 31) with its amendment Regulation (EU) 2020/878

Printing date 17.05.2024

Version number 1.1

Revision: 17.05.2024

Trade name: 5500 AIR BAKE SR CLEAR

· vPvB: Not applicable.

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

CAS: 67-64-1	acetone	>25- <i>≤</i> 50%
EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	♦ Flam. Liq. 2, H225; ↓ Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate 🚸 Flam. Liq. 3, H226; 抄 STOT SE 3, H336	>25- <i>≤</i> 50%
CAS: 110-43-0 EINECS: 203-767-1 Reg.nr.: 01-2119902391-49-0000	2-Heptanone	>10- <i>≤</i> 25%
CAS: 104810-47-1 ELINCS: 400-830-7 Reg.nr.: 01-0000015075-76-0017	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl) propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h- � Aquatic Chronic 2, H411; � Skin Sens. 1, H317	<i>≤</i> 2.5%
CAS: 41556-26-7 Reg.nr.: 01-2119491304-40	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	<i>≤</i> 2.5%
CAS: 100-42-5 EINECS: 202-851-5 Reg.nr.: 01-2119457861-32	styrene Flam. Liq. 3, H226; Repr. 2, H361d; STOT RE 1, H372; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	<i>≤</i> 2.5%
CAS: 103-11-7 EINECS: 203-080-7 Reg.nr.: 01-2119453458-37	2-ethylhexyl acrylate Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	<i>≤</i> 2.5%
CAS: 141-32-2 EINECS: 205-480-7 Reg.nr.: 01-2119453155	n-butyl acrylate	<i>≤</i> 2.5%

(Contd. on page 4)



Page 4/12

Safety data sheet

according to 1907/2006/EC. Article 31) with its amendment

Regulation (EU) 2020/878

Printing date 17.05.2024

Version number 1.1

Revision: 17.05.2024

(Contd. of page 3)

Trade name: 5500 AIR BAKE SR CLEAR

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. • 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

(Contd. on page 5)



Page 5/12

Safety data sheet

according to 1907/2006/EC, Article 31) with its amendment

Regulation (EU) 2020/878

Printing date 17.05.2024

Version number 1.1

Revision: 17.05.2024

Trade name: 5500 AIR BAKE SR CLEAR

(Contd. of page 4)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see section 7.

Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone	
WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm	
123-86-4 n-butyl acetate	
WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm	
110-43-0 2-Heptanone	
WEL Short-term value: 475 mg/m³, 100 ppm Long-term value: 237 mg/m³, 50 ppm Sk	
100-42-5 styrene	
WEL Short-term value: 1080 mg/m³, 250 ppm Long-term value: 430 mg/m³, 100 ppm	
141-32-2 n-butyl acrylate	
WEL Short-term value: 26 mg/m³, 5 ppm Long-term value: 5 mg/m³, 1 ppm	
• Additional information: The lists valid during the making were used as basis.	
	(Contd. on page 6)



Page 6/12

Safety data sheet

according to 1907/2006/EC, Article 31) with its amendment Regulation (EU) 2020/878

Printing date 17.05.2024

Version number 1.1

Revision: 17.05.2024

Trade name: 5500 AIR BAKE SR CLEAR


(Contd. of page 5)

- · 8.2 Exposure controls
- · Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.





Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 7)



Page 7/12

Safety data sheet according to 1907/2006/EC, Article 31) with its amendment Regulation (EU) 2020/878

Printing date 17.05.2024

Version number 1.1

Revision: 17.05.2024

Trade name: 5500 AIR BAKE SR CLEAR

(Contd. of page 6)

• 9.1 Information on basic physical and (chemical properties
General Information	
Form:	Liquid
Colour:	Clear
· Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: 55 °C
Flash point:	24 °C
Flammability (solid, gas):	Flammable.
Auto-ignition temperature:	370 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosiv air/vapour mixtures are possible.
Explosion limits:	
Lower:	1 Vol %
Upper:	13 Vol %
Vapour pressure at 20 °C:	233 hPa
Density at 20 °C:	0.923 g/cm ³
Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.



Page 8/12

Safety data sheet

according to 1907/2006/EC, Article 31) with its amendment

Regulation (EU) 2020/878

Printing date 17.05.2024

Version number 1.1

Revision: 17.05.2024

Trade name: 5500 AIR BAKE SR CLEAR

		(Contd. of page 7)
 Solvent content: Organic solvents: VOC (EC) 	68.5 % 632.2 g/l	
Solids content:	30.3 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 9)



Page 9/12

Safety data sheet

according to 1907/2006/EC, Article 31) with its amendment

Regulation (EU) 2020/878

Printing date 17.05.2024

Version number 1.1

Revision: 17.05.2024

Trade name: 5500 AIR BAKE SR CLEAR

(Contd. of page 8)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small guantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number		
· ADR, IMDG, IATA	UN1263	
· 14.2 UN proper shipping name		
ADR	1263 PAINT	
· IMDG, IATA	PAINT	
· 14.3 Transport hazard class(es)	NOT APPLICABLE	



Page 10/12

Safety data sheet according to 1907/2006/EC, Article 31) with its amendment Regulation (EU) 2020/878

Printing date 17.05.2024

Version number 1.1

Revision: 17.05.2024

Trade name: 5500 AIR BAKE SR CLEAR

	(Contd. of page 9
· ADR, IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	<i>III</i>
 14.5 Environmental hazards: Marine pollutant: 	No
 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category 	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
 14.7 Transport in bulk according to Annex II o Marpol and the IBC Code 	f Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m
 Transport category Tunnel restriction code 	3 D/E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m
· UN "Model Regulation":	UN 1263 PAINT, 3, III

(Contd. on page 11)



Page 11/12

Safety data sheet

according to 1907/2006/EC, Article 31) with its amendment Regulation (EU) 2020/878

Printing date 17.05.2024

Version number 1.1

Revision: 17.05.2024

Trade name: 5500 AIR BAKE SR CLEAR

(Contd. of page 10)

Listed

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

67-64-1 acetone

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 12)



Page 12/12

Safety data sheet according to 1907/2006/EC, Article 31) with its amendment Regulation (EU) 2020/878

Printing date 17.05.2024

Version number 1.1

Revision: 17.05.2024

Trade name: 5500 AIR BAKE SR CLEAR

	(Contd. of page 2
H411	Toxic to aquatic life with long lasting effects.
Depar	tment issuing SDS: Product safety department
· Conta	
	viations and acronyms:
	glement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concern
	national Transport of Dangerous Goods by Rail)
	ternational Civil Aviation Organisation
	cord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning i
	onal Carriage of Dangerous Goods by Road)
IMDG: Ir	nternational Maritime Code for Dangerous Goods
	ternational Air Transport Association
	obally Harmonised System of Classification and Labelling of Chemicals
EINECS	: European Inventory of Existing Commercial Chemical Substances
ELINCS.	European List of Notified Chemical Substances
	nemical Abstracts Service (division of the American Chemical Society)
	latile Organic Compounds (USA, EU)
	rsistent, Bioaccumulative and Toxic
	ery Persistent and very Bioaccumulative
	g. 2: Flammable liquids – Category 2
	g. 3: Flammable liquids – Category 3
	bx. 4: Acute toxicity – Category 4
	2: Skin corrosion/irritation – Category 2
	2: Serious eye damage/eye irritation – Category 2 ns. 1: Skin sensitisation – Category 1
	Reproductive toxicity – Category 2
	E 3: Specific target organ toxicity (single exposure) – Category 3
	E 1: Specific target organ toxicity (repeated exposure) – Category 1
	Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
	Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
	Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
	compared to the previous version altered.