

# S2012 – Blending Thinner



## **Product Description**

This product has been developed to assist the painter in the blending out process of 2K Colours.


---

## **Suitable Substrates:**

For Genrock 2K systems

---

## **Product Application**



500% to RTS mixture

---

- Activate, thin and apply 2k colors and clears in medium coats to opacity with no flash between coats.
- Empty the spray gun leaving little amount of activated paint or clear, with no flash off between coats, add 100% of S2012, shake and apply in light to medium coats to melt down the overspray on the edges.
- Add another 200% of S2012 to spray gun, shake and melt down the remaining overspray with light to medium coats.
- Finally, add S2012 to emptied spray gun and apply to the rest of scuffed mat area.
- For spot repair start and finish with 1.5Bar.
- For normal blending keep the air pressure to 2 bar and reduce to 1.5 when applying the S2012.

All application should be within the sanded/scuffed area.

---



Wear suitable protection

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.

---

# S2012 – Blending Thinner



## Product Characteristics

<b>Specific Gravity:</b>	0.88778kg/cm <sup>3</sup>
<b>Flash Point:</b>	14°C
<b>SDS:</b>	Refer to the Safety Data Sheet

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.