

Page 1/12

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 28.05.2024 Version number 1.1 Revision: 23.05.2024

## SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier CLEARS
- · Trade name: 5000 SUPER FAST CLEAR
- · Article number: 5000
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

  use as paint clear over base
- Sector of Use

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9b Fillers, putties, plasters, modelling clay
- Application of the substance / the mixture refer to the relevant Technical Data Sheet refer to the relevant Technical Data Sheet
- 1.3 Details of the supplier of the safety data sheet General Paint Co. S.A.L -Safety Department-

For further information, please consult our Internet site www.generalpaint.biz

Manufacturer/Supplier: Générale de Peinture,

70 Rue Cortambert 75116 Paris, France Tel:+33(0)175293559

info@generalpaint.biz

- · Further information obtainable from: Product Safety Department
- 1.4 Emergency telephone number:
  During normal opening times:(961) 9 925990 /1/2 009619925990

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008) with its amendment Regulation (EU) 2020/878



Flam. Liq. 2 H225 Highly flammable liquid and vapour.

(Contd. on page 2)



Page 2/12

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 28.05.2024 Version number 1.1 Revision: 23.05.2024

Trade name: 5000 SUPER FAST CLEAR

(Contd. of page 1)



health hazard

Repr. 2 H361d Suspected of damaging the unborn child.



STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

n-butyl acetate toluene

· Hazard statements

H225 Highly flammable liquid and vapour.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P405 Store locked up.

(Contd. on page 3)

LB/AR





## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 28.05.2024 Version number 1.1 Revision: 23.05.2024

Trade name: 5000 SUPER FAST CLEAR

(Contd. of page 2)

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · Additional information:

Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, methyl methacrylate, s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-, 2,3-epoxypropyl neodecanoate, methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate, 2-hydroxyethyl methacrylate. May produce an allergic reaction.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description**: Mixture of substances listed below with nonhazardous additions.

| · Dangerous o | components:  |                    |
|---------------|--|--------------------|
| 123-86-4      | n-butyl acetate  Plam. Liq. 3, H226; STOT SE 3, H336   | >25- <i>≤</i> 50%  |
| 108-88-3      | toluene<br><b>♦</b> Flam. Liq. 2, H225; <b>♦</b> Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1,<br>H304; <b>♦</b> Skin Irrit. 2, H315; STOT SE 3, H336  | >2.5- <i>≤</i> 10% |
| 108-65-6      | 2-methoxy-1-methylethyl acetate  Tlam. Liq. 3, H226  | <i>≤</i> 2.5%      |
| 41556-26-7    | bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate  Aquatic Acute 1, H400; Aquatic Chronic 1, H410;  Skin Sens. 1, H317   | <i>≤</i> 2.5%      |
| 80-62-6       | methyl methacrylate      Flam. Liq. 2, H225;    Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335   | ≤2.5%              |
| 104810-47-1   | s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-Aquatic Chronic 2, H411;  | ≤2.5%              |
| 26761-45-5    | 2,3-epoxypropyl neodecanoate<br>♦ Acute Tox. 3, H331; ♦ Aquatic Chronic 2, H411; ♦ Skin Irrit. 2, H315;<br>Skin Sens. 1, H317  | ≤2.5%              |
| 82919-37-7    | methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate  Aquatic Acute 1, H400; Aquatic Chronic 1, H410;  Skin Sens. 1, H317   | <i>≤</i> 2.5%      |
| 868-77-9      | 2-hydroxyethyl methacrylate  Name of the state of the sta | ≤2.5%              |

(Contd. on page 4)



Page 4/12

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 28.05.2024 Version number 1.1 Revision: 23.05.2024

Trade name: 5000 SUPER FAST CLEAR

(Contd. of page 3)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 5)



Page 5/12

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 28.05.2024 Version number 1.1 Revision: 23.05.2024

Trade name: 5000 SUPER FAST CLEAR

See Section 13 for disposal information.

(Contd. of page 4)

### SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

### · Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data: see section 7.

| · Additional i           | · Additional information about design of technical facilities. No further data, see section 7. |  |  |  |
|--------------------------|--|--|--|--|
| · Ingredients            | · Ingredients with limit values that require monitoring at the workplace:                      |  |  |  |
| 123-86-4 n-butyl acetate |  |  |  |  |
| IOELV (EU)               | Short-term value: 723 mg/m³, 150 ppm<br>Long-term value: 241 mg/m³, 50 ppm                     |  |  |  |
| 108-88-3 to              | luene  |  |  |  |
| IOELV (EU)               | Short-term value: 384 mg/m³, 100 ppm<br>Long-term value: 192 mg/m³, 50 ppm<br>Skin             |  |  |  |
| 108-65-6 2-1             | methoxy-1-methylethyl acetate  |  |  |  |
| IOELV (EU)               | Short-term value: 550 mg/m³, 100 ppm<br>Long-term value: 275 mg/m³, 50 ppm<br>Skin             |  |  |  |

(Contd. on page 6)



Page 6/12

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 28.05.2024 Version number 1.1 Revision: 23.05.2024

Trade name: 5000 SUPER FAST CLEAR

(Contd. of page 5)

### 80-62-6 methyl methacrylate

IOELV (EU) Short-term value: 100 ppm Long-term value: 50 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

#### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

LB/AR

(Contd. on page 7)



Page 7/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 28.05.2024 Version number 1.1 Revision: 23.05.2024

Trade name: 5000 SUPER FAST CLEAR

(Contd. of page 6)

| 9.1 Information on basic physical and   | chemical properties   |
|---|---|
| General Information                     |   |
| Appearance:                             |   |
| Form:                                   | Liquid  |
| Colour:                                 | Clear   |
| Odour:                                  | Characteristic  |
| Odour threshold:                        | Not determined.   |
| pH-value:                               | Not determined.   |
| Change in condition                     |   |
| Melting point/freezing point:           | Undetermined.   |
| Initial boiling point and boiling range | e: 110 °C   |
| Flash point:                            | 4 °C  |
| Flammability (solid, gas):              | Highly flammable.   |
| Auto-ignition temperature:              | 370 °C  |
| Decomposition temperature:              | Not determined.   |
| Ignition temperature:                   | Product is not selfigniting.  |
| Explosive properties:                   | Product is not explosive. However, formation of explosair/vapour mixtures are possible. |
| Explosion limits:                       |   |
| Lower:                                  | 1.2 Vol %   |
| Upper:                                  | 7.5 Vol %   |
| Vapour pressure at 20 °C:               | 10.7 hPa  |
| Density at 20 °C:                       | 0.98 g/cm <sup>3</sup>  |
| Relative density                        | Not determined.   |
| Vapour density                          | Not determined.   |
| Evaporation rate                        | Not determined.   |
| Solubility in / Miscibility with        |   |
| water:                                  | Not miscible or difficult to mix.   |
| Partition coefficient: n-octanol/water: | Not determined.   |
| Viscosity:                              |   |
| Dynamic:                                | Not determined.   |
| Kinematic:                              | Not determined.   |
| Solvent content:                        |   |
| Organic solvents:                       | 53.1 %  |

(Contd. on page 8)



Page 8/12

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 28.05.2024 Version number 1.1 Revision: 23.05.2024

Trade name: 5000 SUPER FAST CLEAR

| (Contd. of page 7)                         |
|--|
| 520.3 g/l                                  |
| 45.6 %                                     |
| No further relevant information available. |
|  |

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

| · LD/LC50  | · LD/LC50 values relevant for classification: |                       |  |  |  |  |
|------------|---|-----------------------|--|--|--|--|
| 123-86-4 ו | 123-86-4 n-butyl acetate                      |                       |  |  |  |  |
| Oral       | LD50  | 13,100 mg/kg (rat)    |  |  |  |  |
| Dermal     | LD50  | >5,000 mg/kg (rabbit) |  |  |  |  |
| Inhalative | LC50/4 h                                      | >21 mg/l (rat)        |  |  |  |  |

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging the unborn child.

· STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 9)



Page 9/12

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 28.05.2024 Version number 1.1 Revision: 23.05.2024

Trade name: 5000 SUPER FAST CLEAR

(Contd. of page 8)

· Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

| SECTION |  |  |
|---------|--|--|
|         |  |  |

· 14.1 UN-Number

· **ADR, IMDG, IATA** UN1263

· 14.2 UN proper shipping name

· **ADR** 1263 PAINT PAINT

(Contd. on page 10)



Page 10/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 28.05.2024 Version number 1.1 Revision: 23.05.2024

Trade name: 5000 SUPER FAST CLEAR

|   | (Contd. of page   |
|---|---|
| 14.3 Transport hazard class(es)   | NOT APPLICABLE  |
| ADR, IMDG, IATA   |   |
| · Class<br>· Label  | 3 Flammable liquids.  |
| · 14.4 Packing group<br>· ADR, IMDG, IATA   | II .  |
| · 14.5 Environmental hazards:<br>· Marine pollutant:  | No  |
| · 14.6 Special precautions for user<br>· Hazard identification number (Kemler code):<br>· EMS Number:<br>· Stowage Category | Warning: Flammable liquids.<br>33<br>F-E, <u>S-E</u><br>B   |
| · 14.7 Transport in bulk according to Annex II or<br>Marpol and the IBC Code  | f<br>Not applicable.  |
| Transport/Additional information:   |   |
| · ADR<br>· Limited quantities (LQ)<br>· Excepted quantities (EQ)  | 5L<br>Code: E2<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 500 ml |
| · Transport category<br>· Tunnel restriction code   | 2<br>D/E  |
| · IMDG<br>· Limited quantities (LQ)<br>· Excepted quantities (EQ)   | 5L<br>Code: E2<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 500 ml |
| · UN "Model Regulation":  | UN 1263 PAINT, 3, II  |

(Contd. on page 11)



Page 11/12

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 28.05.2024 Version number 1.1 Revision: 23.05.2024

Trade name: 5000 SUPER FAST CLEAR

(Contd. of page 10)

## SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- · Department issuing SDS: Product safety department
- Contact: N/A

### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 12)



Page 12/12

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 28.05.2024 Version number 1.1 Revision: 23.05.2024

Trade name: 5000 SUPER FAST CLEAR

(Contd. of page 11)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 2: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1 Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard — Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* Data compared to the previous version altered.

LB/AR