

6000M - 2K Clear Matt



Product Description

6000M is a 2K MATT finish clearcoat. It provides an even matt uniform with no striping and no gray shade. It Matches very well with OEM Matt finishes when applied properly according to TDS instructions.

Suitable Substrates

- GenRock basecoat
- Gen₂O basecoat

Product Application



	100%	50%	15-20%
6000M		H500 – FAST	S719 – FAST S711 – NORMAL S721 - SLOW
		H600 – NORMAL	
		H700 – SLOW	
		H750 – EXTRA SLOW	
		H760 - SPECIAL	



16-18 sec / DIN 4 mm / 20 °C (68 °F)
Potlife: 3h to 5h at 20°C



HVLP 1.3 – 1.5 mm (2 spray passes)
2.0 - 2.5 bar inlet pressure



2 Regular Coats
50 – 60 micron



Wear suitable protection

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.



6000M - 2K Clear Matt

Product Characteristics

VOC(2004/42/EC):	2004/42/IIB (e) (840)550. The EU limit value for this product (product category IIB.e) in ready to use form is max 840g/ltr. The VOC content of this product in ready for use form is max. 550 g/l.
Specific Gravity:	1.01 kg/cm ³
Flash Point:	23°C (73.4 °F)
Solid Content:	48% by weight pre-dilution
Coverage:	6-7 m ² /l at 25-micron film thickness (theoretical)
Gloss level:	23 % ± 5 at 60° angle
SDS:	Refer to the Safety Data Sheet

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.