

Page 1/11


Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.05.2024

Version number 1.2

Revision: 29.05.2024



Flam. Liq. 3 H226 Flammable liquid and vapour.

(Contd. on page 2)

LB/AR



Page 2/11

Safety data sheet


according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.05.2024

Version number 1.2

Revision: 29.05.2024

Trade name: 768 BASECOAT PEARL RED VIOLET



(Contd. on page 3)



according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.05.2024

Version number 1.2

Revision: 29.05.2024

Trade name: 768 BASECOAT PEARL RED VIOLET

(Contd. of page 2)

Page 3/11

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
123-86-4 n-butyl acetate		>50- <i>≤</i> 100%	
	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336		
1330-20-7		>2.5- <i>≤</i> 10%	
	🚸 Flam. Liq. 3, H226; 🚸 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315		
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%	
	🚸 Acute Tox. 4, H332; STOT SE 3, H335		
100-41-4	100-41-4 ethylbenzene		
	📀 Flam. Liq. 2, H225; 🚸 STOT RE 2, H373; Asp. Tox. 1, H304; 🚸 Acute Tox. 4, H332		
· Additional i	information: For the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)

LB/AR



according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.05.2024

Version number 1.2

Revision: 29.05.2024

Trade name: 768 BASECOAT PEARL RED VIOLET

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

(Contd. of page 3)

Page 4/11

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **6.3** Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see section 7.

(Contd. on page 5)



Page 5/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.05.2024

Version number 1.2

Revision: 29.05.2024

Trade name: 768 BASECOAT PEARL RED VIOLET

<u> </u>	(Contd. of page 4
•	s with limit values that require monitoring at the workplace:
123-86-4 n-	butyl acetate
IOELV (EU)	Short-term value: 723 mg/m³, 150 ppm
	Long-term value: 241 mg/m³, 50 ppm
1330-20-7 x	<i>cylene</i>
IOELV (EU)	Short-term value: 442 mg/m ³ , 100 ppm
	Long-term value: 221 mg/m³, 50 ppm
	Skin
100-41-4 et	hylbenzene
IOELV (EU)	Short-term value: 884 mg/m ³ , 200 ppm
	Long-term value: 442 mg/m³, 100 ppm
	Skin
Additional	information: The lists valid during the making were used as basis.
	y protection:
P	brief exposure or low pollution use respiratory filter device. In case of intensive or longe se self-contained respiratory protective device.
Due to mis preparation	brief exposure or low pollution use respiratory filter device. In case of intensive or longe se self-contained respiratory protective device.
degradation of Material of	The se self-contained respiratory protective device. The se self-contained respiratory protective device. The self-contained respiratory protectiv

be checked prior to the application. · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6) - LB/AR



according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.05.2024

Version number 1.2

Revision: 29.05.2024

(Contd. of page 5)

Trade name: 768 BASECOAT PEARL RED VIOLET

· Eye protection:

Tightly sealed goggles

SECTION 9: Physical and chemical properties

General Information	
Appearance:	
Form:	Liquid
Colour:	red -violet
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling ran	ge: 120 °C
Flash point:	27 °C
Flammability (solid, gas):	Flammable.
Auto-ignition temperature:	370 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosiv air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20 °C:	10.7 hPa
Density at 20 °C:	0.984 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.

Page 6/11



Page 7/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.05.2024

Version number 1.2

Revision: 29.05.2024

Trade name: 768 BASECOAT PEARL RED VIOLET

	(Contd. of page	ge 6
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	72.5 %	
VOC (EC)	713.9 g/l	
Solids content:	27.4 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

123-86-4 n-butyl acetate

	-	
Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

· Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

(Contd. on page 8) I B/AR



according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.05.2024

Version number 1.2

Revision: 29.05.2024

(Contd. of page 7)

Page 8/11

Trade name: 768 BASECOAT PEARL RED VIOLET

· Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

· Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity: No further relevant information available.

• 12.2 Persistence and degradability No further relevant information available.

• **12.3 Bioaccumulative potential** No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

· 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA

UN1263

(Contd. on page 9)



Page 9/11

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.05.2024

Version number 1.2

Revision: 29.05.2024

Trade name: 768 BASECOAT PEARL RED VIOLET

	(Contd. of page 8
<i>14.2 UN proper shipping name ADR IMDG, IATA</i>	1263 PAINT PAINT
14.3 Transport hazard class(es)	NOT APPLICABLE
ADR, IMDG, IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	<i>III</i>
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user EMS Number: Stowage Category	Warning: Flammable liquids. F-E, <u>S-E</u> A
<i>14.7 Transport in bulk according to Anne Marpol and the IBC Code</i>	ex II of Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m 3
Tunnel restriction code	D/E
<i>IMDG Limited quantities (LQ) Excepted quantities (EQ)</i>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m

(Contd. on page 10)



Page 10/11

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.05.2024

Version number 1.2

Revision: 29.05.2024

Trade name: 768 BASECOAT PEARL RED VIOLET

(Contd. of page 9)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. · Department issuing SDS: Product safety department · Contact: N/A · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose. 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3

(Contd. on page 11)

LB/AR



according to Regulation (EC) No 1907/2006, Article 31

Printing date 29.05.2024

Version number 1.2

Revision: 29.05.2024

Page 11/11

Trade name: 768 BASECOAT PEARL RED VIOLET

(Contd. of page 10)

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.

LB/AR