

G77G – Polyester Putty Grey



Product Description

This great metal filler is a multi-purpose putty with an extremely smooth application. It can be applied vertically without running and exhibits high resistance to almost all solvents.

Suitable Substrates:

- Iron, steel plate, glass fiber reinforced plastic.
- Original paints or aged topcoat finishes.

Surface Preparation:

- Clean well the surface to be treated with 8241 Genclean. Make sure it is dry and free from.
- Silicone, wax, grease and any extraneous material.
- On basecoats or enamel top coats, sand and clean the surface before applying the filler.

Product Application



1 – 3% General hardener
Potlife 3 - 5 min at 20°C



Application with putty knife



< 30 min at 20°C



4 – 5 min at 1 m.

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.

G77G – Polyester Putty Grey



Initial Sanding with P60 – P120 roughing-out
Final Sanding with P180 – P220 finishing)

Product Characteristics

VOC(2004/42/EC):	2004/42/IIB (b) (250)250. The EU limit value for this product (product category IIB.b) in ready to use form is max 250g/ltr. The VOC content of this product in ready for use form is max. 250 g/l.
Composition	Unsaturated polyester resin and mineral charges.
Specific Weight:	1.88 ± 0.1.
Available Colors:	Beige, Grey.
SDS:	Refer to the Safety Data Sheet.

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.