



G81Y- Smooth Polyester Putty Beige

Product Description

This great polyester filler is a multi-purpose putty with an extremely smooth application. It is easy to sand, and withstands 100°C without deformation.

Suitable Substrates:

- Iron, steel plate, glass fiber reinforced plastic
- Original paints or aged topcoat finishes

Surface Preparation:

- Clean well the surface to be treated with 8241 GenClean. Make sure it is dry and free from
- Silicone, wax, grease and any extraneous material.

Product Application



1:0.03
3% General Hardener



Application with Putty Knife



< 30 min at 20°C



4-5 minutes at 1m.

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.



G81Y- Smooth Polyester Putty Beige



Initial Sanding with P60 – P120 roughing-out
Final Sanding with P180 – P220 finishing

Product Characteristics

VOC(EC):

2004/42/II B (b) (250)250. The EU limit value for this product (product category II B.b) in ready to use form is max 250g/ltr. The VOC content of this product in ready for use form is max. 250 g/l

Specific Gravity:

1.82 kg/cm³

Solids:

88.7%

SDS:

Refer to the Safety Data Sheet

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.