



### **Product Description**

Silicone remover is suitable for cleaning and degreasing solvent based products. Silicone remover has a high performance with anti-static properties combined in one product, which makes it suitable for all repairs in the bodyshop.

### **Suitable Substrates:**

- OEM
- Thermoplastic acrylic finishes and glass reinforced polyester parts. Suitable for degreasing all Primer surfacers prior to finishing.

### **Product Application**



Wear suitable protection

### **Product Characteristics**

#### **Surface**

#### **Preparation:**

Prior to any repair or refinishing, wash down the vehicle to remove all external contaminants (i.e bird droppings, flies, tree sap, etc)

#### **Raw Material:**

Organic Solvents

#### **Cleaning**

#### **Techniques:**

Use before sanding, apply by means of a soaked cloth and remove with a clean dry cloth.

(Wipe on wipe off)

Use also before applying primers and topcoats

#### **Important remarks:**

For professional use only,

Do not allow silicone remover to dry on surfaces.

Change cloth often

#### **VOC(2004/42/EC):**

2004/42/IIB (a) (850)800. The EU limit value for this product (product category IIB.a) in ready to use form is max 850g/ltr. The VOC content of this product in ready for use form is max. 800 g/l.

#### **Flash Point:**

21°C (70°F)

#### **Specific Gravity:**

0.77 kg/cm<sup>3</sup>

#### **SDS:**

Refer to the Safety Data Sheet

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.