

8230 - 2K Plastic Additive




Descripcion:

8230 2K es un aditivo cuyas propiedades permiten aplicar un aparejo 2K directamente sobre zonas plásticas sin necesidad de aplicar un adherente para plásticos 1K.

Uso:

- Con aparejos "General" 2K
- No usar con: 9700 Wash Primer, 1K productos , G908 Epoxy Primer.

Aplicación del product:



1:15
15% 8230 2K Plastic Aditive | 100% 2K Primer.



Spray Nozzle 1.4 – 1.6 mm
2.0 – 2.2 bar inlet pressure



Light dry sanding with P400 - P500 grit



Clean Surface with Genclean 8241 degreaser to remove contamination prior to top coating



Wear suitable protection

Product Characteristics

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.

8230 - 2K Plastic Additive



| | |
|--------------------------|---|
| VOC(2004/42/EC): | 2004/42/IIB (c) (540)540. The EU limit value for this product (product category IIB.c) in ready to use form is max 540g/ltr. The VOC content of this product in ready for use form is max. 540 g/l. |
| Specific Gravity: | 1.105 kg/cm ³ |
| Flash Point: | 20 (77 °F) |
| Solid Content: | 42.5 % by weight pre-dilution |
| Coverage: | 10-11 m ² /l at 25-micron film thickness (theoretical) |
| SDS: | Refer to the Safety Data Sheet |

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.