



2300 - Easy Clear


Descripción:

2300 es un barniz transparente de alto contenido de sólidos fácil de aplicar, buena fluidez y brillo duradero. Se sugiere principalmente para pintores de manos rápidas.

Sustratos Recomendables:

- GenRock basecoat

Aplicación del product:



	100% Clear	50% Hardener	5-10% Thinner
2300		H700 SLOW	S721 SLOW
		H600 NORMAL	S711 NORMAL
		H700 SLOW	S719 FAST




15-16s / DIN 4 mm / 20°C



HVLP 1,3 - 1,4 mm(2 capas)
 0,7 bar de presión de atomización
 1 capa media + completa
 50 µm



Evaporar 2-3 minutos entre capas
 Evaporar 10 minutos antes de hornear
 Hornear 20 minutos a 60°C. Temperatura panel



Onda Corta 10-15 minutos
 Panel > 80cm de distancia al IR

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.



2300 - Easy Clear



Utilizar protección

Características del producto:

Specific Gravity: 0.985 kg/cm³

Flash Point: 25°C (77°F)

Solid Content: 46.2 % by weight

Coverage: 8 - 9 m²/l at 50-micron dry film thickness (theoretical)

SDS: Refer to the Safety Data Sheet

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.