

9340 – Adhesion Promoter




Product Description

9340 is an excellent adhesion promoter based on a polymerized polyolefin resin. It has high solvent resistance, water resistance and corrosion resistance. 9340 offers excellent adhesion not only on metals including galvanized steel, Aluminum, stainless steel, plastics, body bumpers but also on glass, tiles, and acrylic signs

Suitable Substrates:

Galvanized Steel/Aluminum/Plastics including PP/Stainless Steel/Chromium Plating/ Steel/EDP/Old sanded painted surfaces/Glass/Tiles/Acrylic Sign Boards/Copper/1 and 2 component Urethane paint/ 2 component Acrylic urethane paint

Product Application




Ready To Spray



Spray Nozzle 1.3 – 1.4 mm
2.0 – 2.5 bar inlet pressure



1-2 coats – 6-8 microns per coat



5 to 10 minutes at 20 oC (68 oF)

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.

9340 – Adhesion Promoter



After 20 min @ 20°C



Wear suitable protection

Product Characteristics

VOC(2004/42/EC): 2004/42/IIB (c) (540)540. The EU limit value for this product (product category IIB.c) in ready to use form is max 540g/ltr. The VOC content of this product in ready for use form is max. 540 g/l.

Specific Gravity: 0.86kg/cm³

Flash Point: -17°C (1 °F)

Solid Content: 5 % by weight pre-dilution

SDS: Refer to the Safety Data Sheet

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.