



Genrock Basecoat

Product Description

Complete basecoat product range based on 70 + base colors including 16 Pearlescent, iridescent and tinted metallic toners as well as 6 xiralllic. High pigmented system, economy on the quantity of paint ready for use, greater coverage, time saving in application because 2 coats are sufficient and there is minimal waiting time for the application of the top coat.

Surface Preparation:

- Old paint well sanded and surfaces well primed and prepared.

Suitable Substrates:

- Existing Finishes except TPA
- “General” 1 K or 2 K primers
- OEM Primer or EDP, sanded
- “General” Polyester Putties
- Bare metal substrates must be pre-primed with wash primer 9700

Product Application



Mix 75% “Genrock” thinners



18-19 sec / DIN 4 mm / 20o C (68o F)



HVLP 1.3 - 1.4 mm;
2.0 – 2.5 bar inlet pressure




5 min. between coats. For metallic colors, a drop coat is recommended

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.



Genrock Basecoat



Wait until fully matt before applying top coat



Wear suitable protection

Product Characteristics

Flash Point:	23°C (73.4°F)
Solids Content:	21.2-39.0% by weight
Specific Gravity:	0.94-1.16 kg/cm ³ (7.82-9.66 lbs/gal)
Coverage:	8-10 m ² /l at 25 micron dry thickness
SDS:	Refer to the safety data sheet

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.