



G101 – 1K Fine Putty


Product Description

1K fine putty is a nitrocellulose fine glazing putty to fill surface imperfections such as scratch marks and pinholes. 1K fine putty is very fast drying when applied in thin coats. It is easy to apply and easy to sand.

Suitable Substrates:

- Through – hardened sanded paintwork.
- Sanded primed surfaces.


Product Application



Ready to use.



Apply one to three thin coats as necessary.



15 min at 20°C (70°F)
Between coats



20 min at 20°C (70°F)



Dry sand with P 400 to P 500 grit paper.

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.



G101 – 1K Fine Putty



P600 to P800 grit wet.



1K Fine Putty can be recoated with any General primer surfacer or sealer, it can also be directly topcoated General with basecoat solvent.



Wear suitable protection

Product Characteristics

VOC(2004/42/EC): 560 g/l

Flash Point: 28°C (82.4 °F)

Specific Gravity: 1.47 kg/cm³

Solid Content 61.2 % by weight

Available Colors:
G101 Beige
G102 Red

SDS: Refer to the Safety Data Sheet.

Disclaimer: Users assume full responsibility for any consequences resulting from the incorrect usage of our products.