

Page 1/10

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

1 Identification

- · Product identifier
- · Trade name: GO350 FLOP MODIFIER
- · Article number: GO350
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet

• *Manufacturer/Supplier:* General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

• *Classification of the substance or mixture* The product is not classified, according to the Globally Harmonized System (GHS).

· Label elements

- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Classification system:
- NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)

HEALTH 0	Health = 0
FIRE 0	Fire = 0
REACTIVITY 0	Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 2)

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO350 FLOP MODIFIER

(Contd. of page 1)

>2.5-*≤*10%

>2.5-*≤*10%

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

111-76-2 2-butoxyethanol 67-63-0 propan-2-ol

4 First-aid measures

- · Description of first aid measures
- · General information: No special measures required.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Not required.

Environmental precautions: Do not allow to enter sewers/ surface or ground water.
 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Reference to other sections
 No dangerous substances are released.
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.

(Contd. on page 3)



Page 2/10

US

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO350 FLOP MODIFIER

	ion 13 for disposal information. e Action Criteria for Chemicals	(Contd. of page 2)
· PAC-1:		
111-76-2	2-butoxyethanol	60 ppm
67-63-0	propan-2-ol	400 ppm
140-88-5	ethyl acrylate	8.3 ppm
· PAC-2:		
111-76-2	2-butoxyethanol	120 ppm
67-63-0	propan-2-ol	2000* ppm
140-88-5	ethyl acrylate	36 ppm
· PAC-3:		
111-76-2	2-butoxyethanol	700 ppm
67-63-0	propan-2-ol	12000** ppm
140-88-5	ethyl acrylate	240 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Storage class: 12
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol

PEL Long-term value: 240 mg/m³, 50 ppm

Skin

(Contd. on page 4)



Page 3/10



Page 4/10

Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO350 FLOP MODIFIER

TIV	Long-term value: 24 mg/m³, 5 ppm Skin
	Long-term value: 20 ppm BEI, A3
67-6	3-0 propan-2-ol
PEL	Long-term value: 980 mg/m³, 400 ppm
REL	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
TLV	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4
· Ingre	edients with biological limit values:
111-:	76-2 2-butoxyethanol
	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)
	3-0 propan-2-ol
	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
	itional information: The lists that were valid during the creation were used as basis.
 Pers Gene The t Brea Prote 	osure controls onal protective equipment: eral protective and hygienic measures: usual precautionary measures for handling chemicals should be followed. othing equipment: Not required. ection of hands:
Due prepa Selei	glove material has to be impermeable and resistant to the product/ the substance/ the preparation. to missing tests no recommendation to the glove material can be given for the product/ the aration/ the chemical mixture. ction of the glove material on consideration of the penetration times, rates of diffusion and the adation
	erial of gloves

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO350 FLOP MODIFIER

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

General Information Appearance:	
Form:	Fluid
Color:	According to product description
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value at 20 °C (68 °F):	7.4-8.4
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)
Flash point:	Not applicable.
Flammability:	Not applicable.
Auto igniting:	240 °C (464 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
Density at 20 °C (68 °F):	1.0101 g/cm³ (8.42928 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	er): Not determined.



Page 5/10

(Contd. of page 4)



acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Page 6/10

Trade name: GO350 FLOP MODIFIER

		(Contd. of page 5)
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	9.6 %	
Water:	70.2 %	
Coating VOC content:	9.57 %	
-	332.6 g/l / 2.78 lb/gal	
Material VOC content:	96.6 g/l / 0.81 lb/gal	
Solids content:	19.6 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50) values	that are	relevant for	classification:
-----------	----------	----------	--------------	-----------------

111-76-2 2-butoxyethanol

Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (rat)
	LD50	1,200 mg/kg (ATE) 1,480 mg/kg (rat) 400 mg/kg (rab)
Inhalative	LC50/4 h	3 mg/l (ATE)

Primary irritant effect:

- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

(Contd. on page 7)

US

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO350 FLOP MODIFIER

· Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

111-76-2 2-butoxyethanol

67-63-0 propan-2-ol

140-88-5 ethyl acrylate

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Smaller quantities can be disposed of with household waste.

(Contd. on page 8)

US



Page 7/10

(Contd. of page 6)

3

3

2B

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO350 FLOP MODIFIER

(Contd. of page 7)

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

	non applicable NOT APPLICABLE
UN proper shipping name	NOT APPLICABLE
	NOT APPLICABLE NOT APPLICABLE
· · · · · · · · · · · · · · · · · · ·	NON APPLICABILE NOT APPLICABLE
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Not applicable.

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 3	55 (extremely hazardous substances):	
None of the	e ingredients is listed.	
· Section 31	13 (Specific toxic chemical listings):	
111-76-2	2-butoxyethanol	
67-63-0	propan-2-ol	
140-88-5	ethyl acrylate	
· TSCA (To	xic Substances Control Act):	
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE
111-76-2	2-butoxyethanol	ACTIVE
67-63-0	propan-2-ol	ACTIVE
140-88-5	ethyl acrylate	ACTIVE
	(Conte	d. on page 9)



Page 8/10



Page 9/10

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO350 FLOP MODIFIER

ardous Air Pollutants	ontd. of pag
position 65 micals known to cause cancer: -88-5 ethyl acrylate micals known to cause reproductive toxicity for females: e of the ingredients is listed. micals known to cause reproductive toxicity for males: e of the ingredients is listed. micals known to cause reproductive toxicity for males: e of the ingredients is listed. micals known to cause developmental toxicity: e of the ingredients is listed. cinogenic categories A (Environmental Protection Agency) -76-2 2-butoxyethanol 7(Threshold Limit Value) -76-2 2-butoxyethanol -63-0 propan-2-ol -88-5 ethyl acrylate	
micals known to cause cancer: -88-5 ethyl acrylate micals known to cause reproductive toxicity for females: e of the ingredients is listed. micals known to cause reproductive toxicity for males: e of the ingredients is listed. micals known to cause developmental toxicity: e of the ingredients is listed. micals known to cause developmental toxicity: e of the ingredients is listed. cinogenic categories A (Environmental Protection Agency) -76-2 2-butoxyethanol -76-2 2-butoxyethanol -76-2 2-butoxyethanol -63-0 propan-2-ol -88-5 ethyl acrylate	
-88-5 ethyl acrylate micals known to cause reproductive toxicity for females: e of the ingredients is listed. micals known to cause reproductive toxicity for males: e of the ingredients is listed. micals known to cause developmental toxicity: e of the ingredients is listed. micals known to cause developmental toxicity: e of the ingredients is listed. cinogenic categories A (Environmental Protection Agency) -76-2 2-butoxyethanol (Threshold Limit Value) -76-2 2-butoxyethanol 63-0 propan-2-ol e88-5 ethyl acrylate	
micals known to cause reproductive toxicity for females: e of the ingredients is listed. micals known to cause reproductive toxicity for males: e of the ingredients is listed. micals known to cause developmental toxicity: e of the ingredients is listed. micals known to cause developmental toxicity: e of the ingredients is listed. cinogenic categories A (Environmental Protection Agency) -76-2 2-butoxyethanol 7-76-2 2-butoxyethanol 63-0 propan-2-ol 88-5 ethyl acrylate	
e of the ingredients is listed. micals known to cause reproductive toxicity for males: e of the ingredients is listed. micals known to cause developmental toxicity: e of the ingredients is listed. cinogenic categories (Environmental Protection Agency) -76-2 2-butoxyethanol (Threshold Limit Value) -76-2 2-butoxyethanol -63-0 propan-2-ol -88-5 ethyl acrylate	
 micals known to cause reproductive toxicity for males: e of the ingredients is listed. micals known to cause developmental toxicity: e of the ingredients is listed. cinogenic categories (Environmental Protection Agency) -76-2 2-butoxyethanol (Threshold Limit Value) -76-2 2-butoxyethanol 63-0 propan-2-ol -88-5 ethyl acrylate 	
e of the ingredients is listed. micals known to cause developmental toxicity: e of the ingredients is listed. cinogenic categories (Environmental Protection Agency) -76-2 2-butoxyethanol (Threshold Limit Value) -76-2 2-butoxyethanol -63-0 propan-2-ol -88-5 ethyl acrylate	
 micals known to cause developmental toxicity: e of the ingredients is listed. cinogenic categories (Environmental Protection Agency) -76-2 2-butoxyethanol (Threshold Limit Value) -76-2 2-butoxyethanol -63-0 propan-2-ol -88-5 ethyl acrylate 	
e of the ingredients is listed. cinogenic categories (Environmental Protection Agency) -76-2 2-butoxyethanol (Threshold Limit Value) -76-2 2-butoxyethanol -76-2 2-butoxyethanol -63-0 propan-2-ol -88-5 ethyl acrylate	
cinogenic categories (Environmental Protection Agency) 76-2 2-butoxyethanol (Threshold Limit Value) 76-2 2-butoxyethanol 63-0 propan-2-ol -88-5 ethyl acrylate	
(Environmental Protection Agency) -76-2 2-butoxyethanol (Threshold Limit Value) -76-2 2-butoxyethanol -63-0 propan-2-ol -88-5 ethyl acrylate	
-76-2 2-butoxyethanol (Threshold Limit Value) -76-2 2-butoxyethanol -63-0 propan-2-ol -88-5 ethyl acrylate	
-76-2 2-butoxyethanol -63-0 propan-2-ol -88-5 ethyl acrylate	Λ
-63-0 propan-2-ol -88-5 ethyl acrylate	
-88-5 ethyl acrylate	A
	F
SH-Ca (National Institute for Occupational Safety and Health)	F
on ou (nutonal montate for occupational ource) and neurally	· ·
-88-5 ethyl acrylate	
S label elements Void	

- · Hazard statements Void
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 11/16/2024 / 1.0
- Abbreviations and acronyms: EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

(Contd. on page 10)

US



acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Page 10/10

(Contd. of page 9)

Trade name: GO350 FLOP MODIFIER

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit • * Data compared to the previous version altered.

US