

Page 1/10

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

1 Identification

- · Product identifier
- · Trade name: GO370 XIRALLIC COPPER
- · Article number: GO370
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet

• *Manufacturer/Supplier:* General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

Classification of the substance or mixture
 Flammable liquids 4 H227 Combustible liquid.

· Label elements

- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms Void
- · Signal word Warning
- · Hazard statements Combustible liquid.
- · Precautionary statements
- Keep away from flames and hot surfaces. No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)



(Contd. on page 2)

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO370 XIRALLIC COPPER

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

111-76-2 2-butoxyethanol

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required. · Environmental precautions:
- Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

US



(Contd. of page 1)

Page 2/10

>2.5-≤10%



acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO370 XIRALLIC COPPER (Contd. of page 2) · Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. · Reference to other sections No dangerous substances are released. See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. · Protective Action Criteria for Chemicals · PAC-1: 111-76-2 2-butoxyethanol 60 ppm 67-63-0 propan-2-ol 400 ppm 108-01-0 2-dimethylaminoethanol 3.7 ppm 108-65-6 2-methoxy-1-methylethyl acetate 50 ppm 1330-20-7 xylene 130 ppm 100-41-4 ethylbenzene 33 ppm 140-88-5 ethyl acrylate 8.3 ppm · PAC-2; 111-76-2 2-butoxyethanol 120 ppm 67-63-0 propan-2-ol 2000* ppm 108-01-0 2-dimethylaminoethanol 12 ppm 108-65-6 2-methoxy-1-methylethyl acetate 1,000 ppm 1330-20-7 xylene 920* ppm 100-41-4 ethylbenzene 1100* ppm 140-88-5 ethyl acrylate 36 ppm · PAC-3: 111-76-2 2-butoxyethanol 700 ppm 67-63-0 propan-2-ol 12000** ppm 108-01-0 2-dimethylaminoethanol 72 ppm 108-65-6 2-methoxy-1-methylethyl acetate 5000* ppm 1330-20-7 xylene 2500* ppm 100-41-4 ethylbenzene 1800* ppm 140-88-5 ethyl acrylate 240 ppm

(Contd. on page 4)

Page 3/10



Page 4/10

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO370 XIRALLIC COPPER

(Contd. of page 3)

7 Handling and storage

· Handling:

- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol

- PEL Long-term value: 240 mg/m³, 50 ppm Skin
- REL Long-term value: 24 mg/m³, 5 ppm Skin
- TLV Long-term value: 20 ppm BEI, A3

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

- BEI 200 mg/g creatinine Medium: urine Time: end of shift Deremeter: Butowycootio
 - Parameter: Butoxyacetic acid (BAA) (with hydrolysis)
- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.

(Contd. on page 5)

US



Page 5/10

(Contd. of page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO370 XIRALLIC COPPER

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

 Information on basic physical and General Information 	chemical properties	
· Appearance:		
Form:	Fluid	
Color:	According to product description	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value at 20 °C (68 °F):	7.4-8.4	
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 100 °C (212 °F)	
· Flash point:	68 °C (154.4 °F)	
· Flammability:	Not applicable.	
· Auto igniting:	240 °C (464 °F)	
· Decomposition temperature:	Not determined.	
· Ignition temperature:	Product is not selfigniting.	
		(Contd. on page 6



acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO370 XIRALLIC COPPER

	(Contd. of pag
Danger of explosion:	Not determined.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
Density at 20 °C (68 °F):	1.095 g/cm³ (9.13778 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	8.1 %
Water:	71.3 %
Coating VOC content:	8.11 %
-	405.0 g/l / 3.38 lb/gal
Material VOC content:	88.8 g/l / 0.74 lb/gal
Solids content:	20.3 %

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

US

Page 6/10



Page 7/10

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO370 XIRALLIC COPPER

(Contd. of page 6)

xyethanol 1,200 mg/kg (ATE) 1,480 mg/kg (rat)	
1,480 mg/kg (rat)	
400 mg/kg (rab)	
'4 h 3 mg/l (ATE)	
nal Agency for Research on Cancer)	
•	3
	3
	3
acrylate	2
aciviaie	
oxicology Program)	2
	4 h 3 mg/l (ATE) effect:

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.

(Contd. on page 8)

US



acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO370 XIRALLIC COPPER

· Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
 Recommendation:
- Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number	NOT APPLICABLE
· UN proper shipping name	NOT APPLICABLE
 Transport hazard class(es) 	NOT APPLICABLE NOT APPLICABLE
· Packing group	NOT APPLICABLE
 Environmental hazards: Marine pollutant: 	No
· Special precautions for user	Not applicable.
 Transport in bulk according to Annex II MARPOL73/78 and the IBC Code 	l of Not applicable.

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

(Contd. on page 9)

US

Page 8/10

(Contd. of page 7)



Page 9/10

Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO370 XIRALLIC COPPER

Sara		(Contd. of page
	55 (extremely hazardous substances):	
None of th	e ingredients is listed.	
Section 3	13 (Specific toxic chemical listings):	
111-76-2	2-butoxyethanol	
67-63-0	propan-2-ol	
1330-20-7	xylene	
100-41-4	ethylbenzene	
140-88-5	ethyl acrylate	
•	xic Substances Control Act):	
All compo	nents have the value ACTIVE.	
	s Air Pollutants	
1330-20-7		
	ethylbenzene	
	ethyl acrylate	
Propositi		
	s known to cause cancer:	
100-41-4	ethylbenzene	
140-88-5	ethyl acrylate	
Chemical	s known to cause reproductive toxicity for females:	
None of th	e ingredients is listed.	
	s known to cause reproductive toxicity for males:	
None of th	e ingredients is listed.	
Chemical	s known to cause developmental toxicity:	
None of th	e ingredients is listed.	
Carcinoge	enic categories	
	ironmental Protection Agency)	
111-76-2	2-butoxyethanol	N
1330-20-7		1
100-41-4	ethylbenzene	D
TLV (Thre	eshold Limit Value)	· · · · ·
111-76-2	2-butoxyethanol	A
67-63-0	propan-2-ol	A
1330-20-7	xylene	A
100-41-4	ethylbenzene	A



Page 10/10

(Contd. of page 9)

A4

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/16/2024

Reviewed on 11/16/2024

Trade name: GO370 XIRALLIC COPPER

140-88-5 ethyl acrylate

· NIOSH-Ca (National Institute for Occupational Safety and Health)

- 140-88-5 ethyl acrylate
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms Void
- · Signal word Warning
- · Hazard statements
- Combustible liquid.
- Precautionary statements
 - Keep away from flames and hot surfaces. No smoking.
 - Wear protective gloves/protective clothing/eye protection/face protection.
 - In case of fire: Use CO2, powder or water spray to extinguish.
- Store in a well-ventilated place. Keep cool.
- Dispose of contents/container in accordance with local/regional/national/international regulations.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 11/16/2024 / 1.0
- · Abbreviations and acronyms: EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, ÉU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable liquids 4: Flammable liquids - Category 4 • * Data compared to the previous version altered.

us -