



Safety Data Sheet

acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

1 Identification

- **Product identifier** GENROCK 2K
- **Trade name:** 640 2K MOLYBDATE RED
- **Article number:** 640
- **Application of the substance / the mixture** refer to the relevant Technical Data Sheet
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
General Paint Co. S.A.L.
P.O. Box 7623
Beirut
LEBANON
info@generalpaint.biz
- **Information department:** Product Safety Department
- **Emergency telephone number:** 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 1A

H350 May cause cancer.

Toxic to Reproduction 1A

H360 May damage fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

- **Label elements**
- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)



Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 640 2K MOLYBDATE RED

(Contd. of page 1)

· Hazard pictograms

GHS02 GHS07 GHS08

· Signal word *Danger***· Hazard-determining components of labeling:***Lead chromate molybdate sulfate red
ethylbenzene**N-methyl-2-pyrrolidone**Quartz (SiO₂)***· Hazard statements***Flammable liquid and vapor.**Causes skin irritation.**May cause cancer.**May damage fertility or the unborn child.**May cause damage to the hearing organs through prolonged or repeated exposure.***· Precautionary statements***Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Keep container tightly closed.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Do not breathe dust/fume/gas/mist/vapors/spray.**Wash thoroughly after handling.**Wear protective gloves/protective clothing/eye protection/face protection.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**If exposed or concerned: Get medical advice/attention.**Specific treatment (see on this label).**Get medical advice/attention if you feel unwell.**Take off contaminated clothing and wash it before reuse.**If skin irritation occurs: Get medical advice/attention.**In case of fire: Use CO₂, powder or water spray to extinguish.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 3)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 640 2K MOLYBDATE RED

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

| | | |
|------------|--|-----------|
| 12656-85-8 | Lead chromate molybdate sulfate red | >10-≤25% |
| 1330-20-7 | xylene | >10-≤25% |
| 123-86-4 | n-butyl acetate | >10-≤25% |
| 64742-95-6 | Solvent naphtha (petroleum), light arom. | >2.5-≤10% |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | ≤2.5% |
| 100-41-4 | ethylbenzene | ≤2.5% |
| 14808-60-7 | Quartz (SiO ₂) | ≤2.5% |
| 1309-64-4 | antimony trioxide | ≤2.5% |
| 872-50-4 | N-methyl-2-pyrrolidone | ≤2.5% |

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 4)



Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 640 2K MOLYBDATE RED

(Contd. of page 3)

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

• **PAC-1:**

| | | |
|------------|-------------------------------------|-----------------------|
| 12656-85-8 | Lead chromate molybdate sulfate red | 5.4 mg/m ³ |
| 1330-20-7 | xylene | 130 ppm |
| 123-86-4 | n-butyl acetate | 5 ppm |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 50 ppm |

(Contd. on page 5)



Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 640 2K MOLYBDATE RED

| | | |
|------------|-----------------------------|-------------------------|
| | | (Contd. of page 4) |
| 100-41-4 | ethylbenzene | 33 ppm |
| 14808-60-7 | Quartz (SiO ₂) | 0.075 mg/m ³ |
| 1309-64-4 | antimony trioxide | 1.8 mg/m ³ |
| 872-50-4 | N-methyl-2-pyrrolidone | 30 ppm |
| 80-62-6 | methyl methacrylate | 17 ppm |
| 868-77-9 | 2-hydroxyethyl methacrylate | 1.9 mg/m ³ |
| 78-83-1 | butanol | 150 ppm |
| 97-88-1 | n-butyl methacrylate | 19 mg/m ³ |
| 7447-41-8 | lithium chloride | 2.3 mg/m ³ |
| 77-58-7 | dibutyltin dilaurate | 1.1 mg/m ³ |

· PAC-2:

| | | |
|------------|-------------------------------------|-----------------------|
| 12656-85-8 | Lead chromate molybdate sulfate red | 59 mg/m ³ |
| 1330-20-7 | xylene | 920* ppm |
| 123-86-4 | n-butyl acetate | 200 ppm |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 1,000 ppm |
| 100-41-4 | ethylbenzene | 1100* ppm |
| 14808-60-7 | Quartz (SiO ₂) | 8.3 mg/m ³ |
| 1309-64-4 | antimony trioxide | 16 mg/m ³ |
| 872-50-4 | N-methyl-2-pyrrolidone | 32 ppm |
| 80-62-6 | methyl methacrylate | 120 ppm |
| 868-77-9 | 2-hydroxyethyl methacrylate | 21 mg/m ³ |
| 78-83-1 | butanol | 1,300 ppm |
| 97-88-1 | n-butyl methacrylate | 210 mg/m ³ |
| 7447-41-8 | lithium chloride | 17 mg/m ³ |
| 77-58-7 | dibutyltin dilaurate | 8 mg/m ³ |

· PAC-3:

| | | |
|------------|-------------------------------------|-----------------------|
| 12656-85-8 | Lead chromate molybdate sulfate red | 350 mg/m ³ |
| 1330-20-7 | xylene | 2500* ppm |
| 123-86-4 | n-butyl acetate | 3000* ppm |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 5000* ppm |
| 100-41-4 | ethylbenzene | 1800* ppm |
| 14808-60-7 | Quartz (SiO ₂) | 50 mg/m ³ |
| 1309-64-4 | antimony trioxide | 96 mg/m ³ |
| 872-50-4 | N-methyl-2-pyrrolidone | 190 ppm |
| 80-62-6 | methyl methacrylate | 570 ppm |

(Contd. on page 6)



Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 640 2K MOLYBDATE RED

| | | (Contd. of page 5) |
|-----------|-----------------------------|-------------------------|
| 868-77-9 | 2-hydroxyethyl methacrylate | 1,000 mg/m ³ |
| 78-83-1 | butanol | 8000* ppm |
| 97-88-1 | n-butyl methacrylate | 1,300 mg/m ³ |
| 7447-41-8 | lithium chloride | 100 mg/m ³ |
| 77-58-7 | dibutyltin dilaurate | 48 mg/m ³ |

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

12656-85-8 Lead chromate molybdate sulfate red

| | |
|-----|--|
| PEL | Long-term value: 0.005* mg/m ³ Ceiling limit value: 0.1** mg/m ³ *as Cr(VI) **as CrO ₃ ; see 29 CFR 1910.1026 |
|-----|--|

(Contd. on page 7)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 640 2K MOLYBDATE RED

(Contd. of page 6)

| | |
|---|---|
| REL | Long-term value: 0.0002 mg/m ³ as Cr; See Pocket Guide Apps. A and C |
| TLV | Short-term value: 0.0005 mg/m ³ Long-term value: 0.0002 mg/m ³ as Cr(VI); inhalable; A1; DSEN, RSEN |
| 1330-20-7 xylene | |
| PEL | Long-term value: 435 mg/m ³ , 100 ppm |
| REL | Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm |
| TLV | Long-term value: 20 ppm BEI, A4 |
| 123-86-4 n-butyl acetate | |
| PEL | Long-term value: 710 mg/m ³ , 150 ppm |
| REL | Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm |
| TLV | Short-term value: 150 ppm Long-term value: 50 ppm |
| 108-65-6 2-methoxy-1-methylethyl acetate | |
| WEEL | Long-term value: 50 ppm |
| 100-41-4 ethylbenzene | |
| PEL | Long-term value: 435 mg/m ³ , 100 ppm |
| REL | Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm |
| TLV | Long-term value: 20 ppm OTO, BEI, A3 |
| 14808-60-7 Quartz (SiO₂) | |
| PEL | Long-term value: 0.05* mg/m ³ *resp. dust; 30mg/m ³ /%SiO ₂ +2 |
| REL | Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A |
| TLV | Long-term value: 0.025* mg/m ³ *respirable particulate matter, A2 |
| 1309-64-4 antimony trioxide | |
| TLV | Long-term value: 0.02 mg/m ³ inhalable fraction, A2 |
| 872-50-4 N-methyl-2-pyrrolidone | |
| TLV | BEI |

(Contd. on page 8)



Safety Data Sheet

acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 640 2K MOLYBDATE RED

(Contd. of page 7)

| | |
|------|---------------------------------|
| WEEL | Long-term value: 10 ppm Skin |
|------|---------------------------------|

· Ingredients with biological limit values:

12656-85-8 Lead chromate molybdate sulfate red

| | |
|-----|---|
| BEI | 25 µg/L Medium: urine Time: end of shift at end of workweek Parameter: Total chromium (fume) |
|-----|---|

| | |
|-----|---|
| BEI | 10 µg/L Medium: urine Time: increase during shift Parameter: Total chromium (fume) |
|-----|---|

1330-20-7 xylene

| | |
|-----|--|
| BEI | 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids |
|-----|--|

100-41-4 ethylbenzene

| | |
|-----|---|
| BEI | 0.15 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific) |
|-----|---|

872-50-4 N-methyl-2-pyrrolidone

| | |
|-----|--|
| BEI | 100 mg/L Medium: urine Time: end of shift Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone |
|-----|--|

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 9)



Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 640 2K MOLYBDATE RED

(Contd. of page 8)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

| | |
|--------------------------|-----------------|
| · Form: | Liquid |
| · Color: | Red |
| · Odor: | Characteristic |
| · Odor threshold: | Not determined. |

· **pH-value:** Not determined.

· **Change in condition**

| | |
|---------------------------------------|-------------------|
| · Melting point/Melting range: | Undetermined. |
| · Boiling point/Boiling range: | 127 °C (260.6 °F) |

· **Flash point:** 25 °C (77 °F)

· **Flammability:** Flammable.

(Contd. on page 10)



Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 640 2K MOLYBDATE RED

(Contd. of page 9)

| | |
|---|--|
| · Auto igniting: | 370 °C (698 °F) |
| · Decomposition temperature: | Not determined. |
| · Ignition temperature: | Product is not selfigniting. |
| · Danger of explosion: | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| · Explosion limits: | |
| Lower: | 1.1 Vol % |
| Upper: | 7.5 Vol % |
| · Vapor pressure at 20 °C (68 °F): | 10.7 hPa (8 mm Hg) |
| · Density at 20 °C (68 °F): | 1.33 g/cm ³ (11.09885 lbs/gal) |
| · Relative density | Not determined. |
| · Vapor density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 35.1 % |
| Coating VOC content: | 35.10 % |
| | 466.8 g/l / 3.90 lb/gal |
| Material VOC content: | 466.8 g/l / 3.90 lb/gal |
| Solids content: | 64.7 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 11)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 640 2K MOLYBDATE RED

(Contd. of page 10)

· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

12656-85-8 Lead chromate molybdate sulfate red

| | | |
|------|------|--------------------|
| Oral | LD50 | >5,000 mg/kg (rat) |
|------|------|--------------------|

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** No irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

| | | |
|------------|-------------------------------------|----|
| 12656-85-8 | Lead chromate molybdate sulfate red | 1 |
| 1330-20-7 | xylene | 3 |
| 100-41-4 | ethylbenzene | 2B |
| 14808-60-7 | Quartz (SiO ₂) | 1 |
| 1309-64-4 | antimony trioxide | 2B |
| 80-62-6 | methyl methacrylate | 3 |
| 97-88-1 | n-butyl methacrylate | 2B |

· **NTP (National Toxicology Program)**

| | | |
|------------|-------------------------------------|---|
| 12656-85-8 | Lead chromate molybdate sulfate red | K |
| 14808-60-7 | Quartz (SiO ₂) | K |
| 1309-64-4 | antimony trioxide | R |

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

(Contd. on page 12)



Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 640 2K MOLYBDATE RED


(Contd. of page 11)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT** Paint
- **ADR** 1263 PAINT, ENVIRONMENTALLY HAZARDOUS
- **IMDG, IATA** PAINT
- **Transport hazard class(es)** NOT APPLICABLE
- **DOT**
- 
- **Class** 3 Flammable liquids

(Contd. on page 13)



Safety Data Sheet




acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 640 2K MOLYBDATE RED

(Contd. of page 12)

| | |
|---|--|
| · Label | 3 |
| · ADR, IMDG | |
|   | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · IATA | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group | |
| · DOT, ADR, IMDG, IATA | III |
| · Environmental hazards: | |
| · Marine pollutant: | No Symbol (fish and tree) |
| · Special marking (ADR): | Symbol (fish and tree) |
| · Special precautions for user | Warning: Flammable liquids |
| · Hazard identification number (Kemler code): | 30 |
| · EMS Number: | F-E, S-E |
| · Stowage Category | A |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · DOT | |
| · Quantity limitations | On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L |
| · ADR | |
| · Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |

(Contd. on page 14)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 640 2K MOLYBDATE RED

(Contd. of page 13)

- | | |
|--|--|
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | <p>5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p> |
| <ul style="list-style-type: none"> · UN "Model Regulation": | <p>UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS</p> |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

| | |
|------------|-------------------------------------|
| 12656-85-8 | Lead chromate molybdate sulfate red |
| 1330-20-7 | xylene |
| 100-41-4 | ethylbenzene |
| 1309-64-4 | antimony trioxide |
| 872-50-4 | N-methyl-2-pyrrolidone |
| 80-62-6 | methyl methacrylate |

· **TSCA (Toxic Substances Control Act):**

| | | |
|------------|-------------------------------------|--------|
| 12656-85-8 | Lead chromate molybdate sulfate red | ACTIVE |
| 1330-20-7 | xylene | ACTIVE |
| 123-86-4 | n-butyl acetate | ACTIVE |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | ACTIVE |
| 100-41-4 | ethylbenzene | ACTIVE |
| 14808-60-7 | Quartz (SiO ₂) | ACTIVE |
| 1309-64-4 | antimony trioxide | ACTIVE |
| 872-50-4 | N-methyl-2-pyrrolidone | ACTIVE |
| 80-62-6 | methyl methacrylate | ACTIVE |
| 868-77-9 | 2-hydroxyethyl methacrylate | ACTIVE |
| 78-83-1 | butanol | ACTIVE |
| 136-53-8 | ZINC 2-ETHYLEXANOATE | ACTIVE |
| 97-88-1 | n-butyl methacrylate | ACTIVE |

(Contd. on page 15)



Safety Data Sheet
acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 640 2K MOLYBDATE RED

(Contd. of page 14)

| | | |
|------------|--|--------|
| 64742-88-7 | Solvent naphtha (petroleum), medium aliph. | ACTIVE |
| 7447-41-8 | lithium chloride | ACTIVE |
| 77-58-7 | dibutyltin dilaurate | ACTIVE |

· Hazardous Air Pollutants

| | |
|------------|-------------------------------------|
| 12656-85-8 | Lead chromate molybdate sulfate red |
| 1330-20-7 | xylene |
| 100-41-4 | ethylbenzene |
| 1309-64-4 | antimony trioxide |
| 80-62-6 | methyl methacrylate |

· Proposition 65

· Chemicals known to cause cancer:

| | |
|------------|-------------------------------------|
| 12656-85-8 | Lead chromate molybdate sulfate red |
| 100-41-4 | ethylbenzene |
| 14808-60-7 | Quartz (SiO ₂) |
| 1309-64-4 | antimony trioxide |

· Chemicals known to cause reproductive toxicity for females:

| | |
|------------|-------------------------------------|
| 12656-85-8 | Lead chromate molybdate sulfate red |
|------------|-------------------------------------|

· Chemicals known to cause reproductive toxicity for males:

| | |
|------------|-------------------------------------|
| 12656-85-8 | Lead chromate molybdate sulfate red |
|------------|-------------------------------------|

· Chemicals known to cause developmental toxicity:

| | |
|------------|-------------------------------------|
| 12656-85-8 | Lead chromate molybdate sulfate red |
| 872-50-4 | N-methyl-2-pyrrolidone |

· Carcinogenic categories

· EPA (Environmental Protection Agency)

| | | |
|------------|-------------------------------------|--------------------------------------|
| 12656-85-8 | Lead chromate molybdate sulfate red | A(inh), D(oral), K/L(inh), CBD(oral) |
| 1330-20-7 | xylene | I |
| 100-41-4 | ethylbenzene | D |
| 80-62-6 | methyl methacrylate | E, NL |

· TLV (Threshold Limit Value)

| | | |
|------------|-------------------------------------|----|
| 12656-85-8 | Lead chromate molybdate sulfate red | A1 |
| 1330-20-7 | xylene | A4 |
| 100-41-4 | ethylbenzene | A3 |
| 14808-60-7 | Quartz (SiO ₂) | A2 |
| 1309-64-4 | antimony trioxide | A2 |
| 80-62-6 | methyl methacrylate | A4 |

(Contd. on page 16)



Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 640 2K MOLYBDATE RED

(Contd. of page 15)

| | | |
|---|-------------------------------------|----|
| 77-58-7 | dibutyltin dilaurate | A4 |
| · NIOSH-Ca (National Institute for Occupational Safety and Health) | | |
| 12656-85-8 | Lead chromate molybdate sulfate red | |
| 14808-60-7 | Quartz (SiO ₂) | |

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms

GHS02 GHS07 GHS08

Signal word Danger**Hazard-determining components of labeling:**

Lead chromate molybdate sulfate red

ethylbenzene

N-methyl-2-pyrrolidone

Quartz (SiO₂)**Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

May cause cancer.

May damage fertility or the unborn child.

May cause damage to the hearing organs through prolonged or repeated exposure.

Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

(Contd. on page 17)

US



Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 640 2K MOLYBDATE RED

(Contd. of page 16)

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

• **National regulations:**

• **Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

• **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

• **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Department issuing SDS:** *Product safety department*

• **Contact:** *N/A*

• **Date of preparation / last revision** *10/22/2024 / 1.0*

• **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Skin Irritation 2: Skin corrosion/irritation – Category 2

Carcinogenicity 1A: Carcinogenicity – Category 1A

Toxic to Reproduction 1A: Reproductive toxicity – Category 1A

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

• *** Data compared to the previous version altered.**