

Page 1/14

# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

#### 1 Identification

· Product identifier

- · Trade name: 773 BASECOAT PEARL GOLD
- · Article number: 773
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet

• *Manufacturer/Supplier:* General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

#### 2 Hazard(s) identification

· Classification of the substance or mixture GHS02 Flame Flammable Liquids 3 H226 Flammable liquid and vapor. GHS08 Health hazard Carcinogenicity 2 H351 Suspected of causing cancer. Specific Target Organ Toxicity - Repeated Exposure H373 May cause damage to the hearing organs 2 through prolonged or repeated exposure. GHS07 Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2) US



acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Page 2/14

#### Trade name: 773 BASECOAT PEARL GOLD

Reactivity = 0

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 GHS08 Signal word Warning · Hazard-determining components of labeling: n-butyl acetate ethylbenzene · Hazard statements Flammable liquid and vapor. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 0Fire = 3

US

(Contd. on page 3)



acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Page 3/14

(Contd. of page 2)

#### Trade name: 773 BASECOAT PEARL GOLD

· HMIS-ratings (scale 0 - 4)

HEALTHImage: OFIRE3FIRE3REACTIVITY0Reactivity0

#### · Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.

#### 3 Composition/information on ingredients

#### · Chemical characterization: Mixtures

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
123-86-4	n-butyl acetate	>50- <i>≤</i> 100%
1330-20-7	xylene	>2.5- <i>≤</i> 10%
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%
100-41-4	ethylbenzene	<i>≤</i> 2.5%

#### 4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 4)



Page 4/14

## Safety Data Sheet

acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

#### Trade name: 773 BASECOAT PEARL GOLD

(Contd. of page 3)

#### 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

- Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

#### · Protective Action Criteria for Chemicals

· PAC-1:		
123-86-4	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
107-98-2	1-methoxy-2-propanol	100 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
7664-38-2	phosphoric acid	3 mg/m <sup>3</sup>
70657-70-4	2-methoxypropyl acetate	50 ppm
· PAC-2:		
123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm
107-98-2	1-methoxy-2-propanol	160 ppm
		(Contd. on page 5)



acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Page 5/14

#### Trade name: 773 BASECOAT PEARL GOLD

108-65-6	2-methoxy-1-methylethyl acetate	(Contd. of page 4) 1,000 ppm
	phosphoric acid	30 mg/m <sup>3</sup>
	2-methoxypropyl acetate	1,000 ppm
· PAC-3:		
123-86-4	n-butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
107-98-2	1-methoxy-2-propanol	660 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
	phosphoric acid	150 mg/m³
70657-70-4	2-methoxypropyl acetate	5,000 ppm

#### 7 Handling and storage

· Handling:

- Precautions for safe handling
   Ensure good ventilation/exhaustion at the workplace.
   Open and handle receptacle with care.
   Prevent formation of aerosols.
   Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

(Contd. on page 6)



# Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

#### Trade name: 773 BASECOAT PEARL GOLD

	is time, the remaining constituent has no known exposure limits.	(Contd. of pag
	86-4 n-butyl acetate	
	Long-term value: 710 mg/m³, 150 ppm	
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm	
TLV	Short-term value: 150 ppm Long-term value: 50 ppm	
1330	-20-7 xylene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Long-term value: 20 ppm BEI, A4	
100-4	41-4 ethylbenzene	
PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm	
REL	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Long-term value: 20 ppm OTO, BEI, A3	
Ingre	edients with biological limit values:	
1330	-20-7 xylene	
	1.5 g/g creatinine Medium: urine	
	Time: end of shift	
	Parameter: Methylhippuric acids	
100-4	41-4 ethylbenzene	
BEI	0.15 g/g creatinine	
	Medium: urine	
	Time: end of shift at end of workweek	
	Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)	
Addi	<b>tional information:</b> The lists that were valid during the creation were used as basis	).
	osure controls	
	onal protective equipment:	
	eral protective and hygienic measures:	
	away from foodstuffs, beverages and feed.	
	ediately remove all soiled and contaminated clothing. h hands before breaks and at the end of work.	
	protective clothing separately.	
0.016		(Contd. on pag

Page 6/14



acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Page 7/14

(Contd. of page 6)

#### Trade name: 773 BASECOAT PEARL GOLD

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • **Protection of hands:** 



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### · Eye protection:



Tightly sealed goggles

### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information

· Appearance:		
Form:	Liquid	
Color:	Gold colored	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	124 °C (255.2 °F)	
		(Contd. on page 8)

<u> us</u>



acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Page 8/14

#### Trade name: 773 BASECOAT PEARL GOLD

	(Contd. of page 7)
· Flash point:	27 °C (80.6 °F)
· Flammability:	Flammable.
· Auto igniting:	370 °C (698 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.
· Explosion limits: Lower: Upper:	1.2 Vol % 7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
<ul> <li>Density at 20 °C (68 °F):</li> <li>Relative density</li> <li>Vapor density</li> <li>Evaporation rate</li> </ul>	0.965 g/cm³ (8.05293 lbs/gal) Not determined. Not determined. Not determined.
<ul> <li>Solubility in / Miscibility with Water:</li> </ul>	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wat	er): Not determined.
<ul> <li>Viscosity:</li> <li>Dynamic:</li> <li>Kinematic:</li> </ul>	Not determined. Not determined.
<ul> <li>Solvent content: Organic solvents: Coating VOC content:</li> <li>Material VOC content;</li> </ul>	72.4 % 72.39 % 698.5 g/l / 5.83 lb/gal 698.5 g/l / 5.83 lb/gal
Solids content:	27.6 %
· Other information	No further relevant information available.

### 10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 9)

- US



acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Page 9/14

(Contd. of page 8)

#### Trade name: 773 BASECOAT PEARL GOLD

- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

#### · LD/LC50 values that are relevant for classification:

123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)

Inhalative LC50/4 h >21 mg/l (rat)

· Primary irritant effect:

- on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

· Carcinogenic categories

· IARC (Inte	rnational Agency for Research on Cancer)	
1330-20-7		3
100-41-4	ethylbenzene	2B
· NTP (Natio	onal Toxicology Program)	
None of the	e ingredients is listed.	
	(Occupational Safety & Health Administration)	
None of the	e ingredients is listed.	

#### 2 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.

(Contd. on page 10)

US



Page 10/14

(Contd. of page 9)

# Safety Data Sheet

acc. to OSHA HCS

*Printing date 10/22/2024* 

Reviewed on 07/29/2024

#### Trade name: 773 BASECOAT PEARL GOLD

· Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

· Results of PBT and vPvB assessment

· PBT: Not applicable.

- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- Waste treatment methods
   Recommendation:
- Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

· UN-Number · DOT, ADR, IMDG, IATA	UN1263	
· UN proper shipping name · DOT · ADR · IMDG, IATA	Paint 1263 PAINT PAINT	
<ul> <li>Transport hazard class(es)</li> <li>DOT</li> </ul>	NOT APPLICABLE	
· Class	3 Flammable liquids	



Page 11/14

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

#### Trade name: 773 BASECOAT PEARL GOLD

	(Contd. of page
Label	3
ADR, IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards: Marine pollutant:	No
Special precautions for user EMS Number:	Warning: Flammable liquids F-E,S-E
Stowage Category	A
<i>Transport in bulk according to Annex</i> <i>MARPOL73/78 and the IBC Code</i>	r <b>II of</b> Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
ADR Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

## 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

(Contd. on page 12)

US



Page 12/14

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

## Trade name: 773 BASECOAT PEARL GOLD

Sara	(Contd. of page 1
Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
Section 313 (Specific toxic chemical listings):	
1330-20-7 xylene	
100-41-4 ethylbenzene	
7664-38-2 phosphoric acid	
TSCA (Toxic Substances Control Act):	
123-86-4 n-butyl acetate	ACTIVE
1330-20-7 xylene	ACTIVE
100-41-4 ethylbenzene	ACTIVE
107-98-2 1-methoxy-2-propanol	ACTIVI
108-65-6 2-methoxy-1-methylethyl acetate	ACTIVE
7664-38-2 phosphoric acid	ACTIVE
Hazardous Air Pollutants	
1330-20-7 xylene	
100-41-4 ethylbenzene	
Proposition 65	
Chemicals known to cause cancer:	
100-41-4 ethylbenzene	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
Carcinogenic categories	
EPA (Environmental Protection Agency)	
1330-20-7 xylene	1
100-41-4 ethylbenzene	[,
TLV (Threshold Limit Value)	
1330-20-7 xylene	A
100-41-4 ethylbenzene	A
NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	




acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Page 13/14

#### Trade name: 773 BASECOAT PEARL GOLD



(Contd. on page 14)



Page 14/14

## Safety Data Sheet

acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

#### Trade name: 773 BASECOAT PEARL GOLD

(Contd. of page 13)

119

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
Department issuing SDS: Product safety department
Contact: N/A

· Date of preparation / last revision 10/22/2024 / 1.0

 Abbreviations and acronvms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 Carcinogenicity 2: Carcinogenicity - Category 2 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2 \* \* Data compared to the previous version altered.