



## Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

### 1 Identification

- **Product identifier**
- **Trade name:** 872 BASECOAT XIRALLIC WHITE
- **Article number:** 872
- **Application of the substance / the mixture** refer to the relevant Technical Data Sheet
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
General Paint Co. S.A.L.  
P.O. Box 7623  
Beirut  
LEBANON  
info@generalpaint.biz
- **Information department:** Product Safety Department
- **Emergency telephone number:** 1-800-535-5053 contract number (89244)

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer.

Specific Target Organ Toxicity - Repeated Exposure H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

**Trade name: 872 BASECOAT XIRALLIC WHITE**

(Contd. of page 1)

**· Hazard pictograms**

GHS02 GHS07 GHS08

**· Signal word** Warning**· Hazard-determining components of labeling:***n*-butyl acetate  
ethylbenzene**· Hazard statements***Flammable liquid and vapor.*  
*Suspected of causing cancer.*  
*May cause drowsiness or dizziness.*  
*May cause damage to the hearing organs through prolonged or repeated exposure.***· Precautionary statements***Obtain special instructions before use.*  
*Do not handle until all safety precautions have been read and understood.*  
*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*  
*Ground/bond container and receiving equipment.*  
*Use explosion-proof electrical/ventilating/lighting/equipment.*  
*Use only non-sparking tools.*  
*Take precautionary measures against static discharge.*  
*Do not breathe dust/fume/gas/mist/vapors/spray.*  
*Use only outdoors or in a well-ventilated area.*  
*Wear protective gloves/protective clothing/eye protection/face protection.*  
*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*  
*IF INHALED: Remove person to fresh air and keep comfortable for breathing.*  
*IF exposed or concerned: Get medical advice/attention.*  
*Call a poison center/doctor if you feel unwell.*  
*Get medical advice/attention if you feel unwell.*  
*In case of fire: Use CO2, powder or water spray to extinguish.*  
*Store in a well-ventilated place. Keep container tightly closed.*  
*Store in a well-ventilated place. Keep cool.*  
*Store locked up.*  
*Dispose of contents/container in accordance with local/regional/national/international regulations.***· Classification system:****· NFPA ratings (scale 0 - 4)**Health = 0  
Fire = 3  
Reactivity = 0

(Contd. on page 3)



## Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

**Trade name: 872 BASECOAT XIRALLIC WHITE**

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	0	Health = 0
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

123-86-4	n-butyl acetate	>50-≤100%
1330-20-7	xylene	>2.5-≤10%
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5-≤10%
108-65-6	2-methoxy-1-methylethyl acetate	>2.5-≤10%
100-41-4	ethylbenzene	≤2.5%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

US

(Contd. on page 4)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

**Trade name: 872 BASECOAT XIRALLIC WHITE**

(Contd. of page 3)

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

123-86-4	<i>n</i> -butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
100-41-4	ethylbenzene	33 ppm
107-98-2	1-methoxy-2-propanol	100 ppm
7664-38-2	phosphoric acid	3 mg/m <sup>3</sup>
70657-70-4	2-methoxypropyl acetate	50 ppm

- **PAC-2:**

123-86-4	<i>n</i> -butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
100-41-4	ethylbenzene	1100* ppm

(Contd. on page 5)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

**Trade name: 872 BASECOAT XIRALLIC WHITE**

(Contd. of page 4)

107-98-2	1-methoxy-2-propanol	160 ppm
7664-38-2	phosphoric acid	30 mg/m <sup>3</sup>
70657-70-4	2-methoxypropyl acetate	1,000 ppm
<b>· PAC-3:</b>		
123-86-4	n-butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
100-41-4	ethylbenzene	1800* ppm
107-98-2	1-methoxy-2-propanol	660 ppm
7664-38-2	phosphoric acid	150 mg/m <sup>3</sup>
70657-70-4	2-methoxypropyl acetate	5,000 ppm

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

(Contd. on page 6)

-US-



## Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

**Trade name: 872 BASECOAT XIRALLIC WHITE**

(Contd. of page 5)

At this time, the remaining constituent has no known exposure limits.

**123-86-4 n-butyl acetate**

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

**1330-20-7 xylene**

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 20 ppm BEI, A4

**108-65-6 2-methoxy-1-methylethyl acetate**

WEEL	Long-term value: 50 ppm
------	-------------------------

**100-41-4 ethylbenzene**

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 20 ppm OTO, BEI, A3

**· Ingredients with biological limit values:**

**1330-20-7 xylene**

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

**100-41-4 ethylbenzene**

BEI	0.15 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)
-----	---

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.

(Contd. on page 7)



# Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

**Trade name: 872 BASECOAT XIRALLIC WHITE**

(Contd. of page 6)

Store protective clothing separately.

• **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

• **Information on basic physical and chemical properties**

• **General Information**

• **Appearance:**

Form: Liquid

Color: White

• **Odor:** Characteristic

• **Odor threshold:** Not determined.

• **pH-value:** Not determined.

• **Change in condition**

Melting point/Melting range: Undetermined.

(Contd. on page 8)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

**Trade name: 872 BASECOAT XIRALLIC WHITE**

(Contd. of page 7)

<b>Boiling point/Boiling range:</b>	120 °C (248 °F)
· <b>Flash point:</b>	27 °C (80.6 °F)
· <b>Flammability:</b>	Flammable.
· <b>Auto igniting:</b>	370 °C (698 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Ignition temperature:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1.2 Vol %
<b>Upper:</b>	7.5 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	10.7 hPa (8 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	0.962 g/cm <sup>3</sup> (8.02789 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	74.3 %
<b>Coating VOC content:</b>	74.27 %
	714.5 g/l / 5.96 lb/gal
<b>Material VOC content:</b>	714.5 g/l / 5.96 lb/gal
<b>Solids content:</b>	25.7 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.

(Contd. on page 9)

US





## Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

**Trade name: 872 BASECOAT XIRALLIC WHITE**

(Contd. of page 8)

- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

#### 123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 10)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

**Trade name: 872 BASECOAT XIRALLIC WHITE**

(Contd. of page 9)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT** Paint
- **ADR** 1263 PAINT
- **IMDG, IATA** PAINT
- **Transport hazard class(es)** NOT APPLICABLE
- **DOT**
- **Class** 3 Flammable liquids



(Contd. on page 11)



## Safety Data Sheet


acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

**Trade name: 872 BASECOAT XIRALLIC WHITE**

(Contd. of page 10)

· <b>Label</b>	3
· <b>ADR, IMDG, IATA</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>Packing group</b>	
· <b>DOT, ADR, IMDG, IATA</b>	III
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>Hazard identification number (Kemler code):</b>	86
· <b>EMS Number:</b>	F-E, S-E
· <b>Stowage Category</b>	A
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	
Not applicable.	
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, III

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.

(Contd. on page 12)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

**Trade name: 872 BASECOAT XIRALLIC WHITE**

(Contd. of page 11)

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

100-41-4 ethylbenzene

7664-38-2 phosphoric acid

· **TSCA (Toxic Substances Control Act):**

123-86-4 n-butyl acetate

ACTIVE

1330-20-7 xylene

ACTIVE

108-65-6 2-methoxy-1-methylethyl acetate

ACTIVE

100-41-4 ethylbenzene

ACTIVE

107-98-2 1-methoxy-2-propanol

ACTIVE

7664-38-2 phosphoric acid

ACTIVE

· **Hazardous Air Pollutants**

1330-20-7 xylene

100-41-4 ethylbenzene

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4 ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7 xylene

I

100-41-4 ethylbenzene

D

· **TLV (Threshold Limit Value)**

1330-20-7 xylene

A4

100-41-4 ethylbenzene

A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

(Contd. on page 13)



## Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

**Trade name: 872 BASECOAT XIRALLIC WHITE**

(Contd. of page 12)

**· GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

**· Hazard pictograms**

GHS02 GHS07 GHS08

**· Signal word** Warning**· Hazard-determining components of labeling:**

*n*-butyl acetate  
ethylbenzene

**· Hazard statements**

Flammable liquid and vapor.  
Suspected of causing cancer.  
May cause drowsiness or dizziness.  
May cause damage to the hearing organs through prolonged or repeated exposure.

**· Precautionary statements**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF exposed or concerned: Get medical advice/attention.  
Call a poison center/doctor if you feel unwell.  
Get medical advice/attention if you feel unwell.  
In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

US

(Contd. on page 14)



## Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

**Trade name: 872 BASECOAT XIRALLIC WHITE**

(Contd. of page 13)

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Department issuing SDS:** Product safety department

• **Contact:** N/A

• **Date of preparation / last revision** 10/23/2024 / 1.1

• **Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organisation*

*ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*VOC: Volatile Organic Compounds (USA, EU)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*NIOSH: National Institute for Occupational Safety*

*OSHA: Occupational Safety & Health*

*TLV: Threshold Limit Value*

*PEL: Permissible Exposure Limit*

*REL: Recommended Exposure Limit*

*BEI: Biological Exposure Limit*

*Flammable Liquids 3: Flammable liquids – Category 3*

*Carcinogenicity 2: Carcinogenicity – Category 2*

*Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3*

*Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2*

• **\* Data compared to the previous version altered.**