

Page 1/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

1 Identification

- · Product identifier
- · Trade name: 894 BASECOAT SILVER DOLLAR COARSE
- · Article number: 894
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet

Manufacturer/Supplier: General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· Classification of the substance or mixture		
GHS02 Flame		
Flammable Liquids 3	H226	Flammable liquid and vapor.
GHS08 Health hazard		
Carcinogenicity 2	H351	Suspected of causing cancer.
Specific Target Organ Toxicity - Repeated Exposur 1	e H372-H373	³ Causes damage to the central nervous system through prolonged or repeated exposure. May cause damage to the hearing organs through prolonged or repeated exposure.
GHS07		
Skin Irritation 2	H315	Causes skin irritation.
Specific Target Organ Toxicity - Single Exposure 3	H336	May cause drowsiness or dizziness. (Contd. on page 2)



Page 2/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Trade name: 894 BASECOAT SILVER DOLLAR COARSE

Reviewed on 07/30/2024

(Contd. of page 1) · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labeling: n-butyl acetate ethylbenzene Naphtha (petroleum), hydrodesulfurized heavy · Hazard statements Flammable liquid and vapor. Causes skin irritation. Suspected of causing cancer. May cause drowsiness or dizziness. Causes damage to the central nervous system through prolonged or repeated exposure. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionarv statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. (Contd. on page 3)



Safety Data Sheet


acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

Page 3/15

Trade name: 894 BASECOAT SILVER DOLLAR COARSE



3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
	n-butyl acetate	>50- <i>≤</i> 100%
1330-20-7	xylene	>10- <i>≤</i> 25%
	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%
7429-90-5	aluminium powder (stabilised)	>2.5- <i>≤</i> 10%
100-41-4	ethylbenzene	>2.5- <i>≤</i> 10%
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	<i>≤</i> 2.5%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 4)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

Trade name: 894 BASECOAT SILVER DOLLAR COARSE

(Contd. of page 3)

Page 4/15

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
 Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

Mount respin Wear protect Environmen Methods an Absorb with Dispose con Ensure adect Reference to See Section See Section See Section	recautions, protective equipment and emergency procedures ratory protective device. tive equipment. Keep unprotected persons away. Intal precautions: Do not allow to enter sewers/ surface or ground water. Ind material for containment and cleaning up: liquid-binding material (sand, diatomite, acid binders, universal binders, sawde taminated material as waste according to section 13. quate ventilation. To other sections 7 for information on safe handling. 8 for information on personal protection equipment. 13 for disposal information. Action Criteria for Chemicals	ust).
· PAC-1:		
123-86-4	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
71-36-3	butan-1-ol	60 ppm
	(C	contd. on page 5)



Page 5/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

Trade name: 894 BASECOAT SILVER DOLLAR COARSE

407.00.0		(Contd. of page
	1-methoxy-2-propanol	100 ppr
	1,2,4-trimethylbenzene	140 ppm
	2-methoxy-1-methylethyl acetate	50 ppm
7664-38-2	phosphoric acid	3 mg/m ³
70657-70-4	2-methoxypropyl acetate	50 ppm
PAC-2:		
123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppn
71-36-3	butan-1-ol	800 ppm
107-98-2	1-methoxy-2-propanol	160 ppm
95-63-6	1,2,4-trimethylbenzene	360 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
7664-38-2	phosphoric acid	30 mg/m ³
70657-70-4	2-methoxypropyl acetate	1,000 ppm
PAC-3:		
123-86-4	n-butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
71-36-3	butan-1-ol	8000** ppn
107-98-2	1-methoxy-2-propanol	660 ppm
95-63-6	1,2,4-trimethylbenzene	480 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
7664-38-2	phosphoric acid	150 mg/m³
70657-70-4	2-methoxypropyl acetate	5,000 ppm

7 Handling and storage

· Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
 Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges.

Keep respiratory protective device available.

(Contd. on page 6)

⁻ US



Page 6/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

Trade name: 894 BASECOAT SILVER DOLLAR COARSE

(Contd. of page 5)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- **Components with limit values that require monitoring at the workplace:** The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

	•	
123-8	86-4 n-butyl acetate	
PEL	Long-term value: 710 mg/m³, 150 ppm	
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm	
TLV	Short-term value: 150 ppm Long-term value: 50 ppm	
1330	-20-7 xylene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Long-term value: 20 ppm BEI, A4	
100-4	41-4 ethylbenzene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
REL	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Long-term value: 20 ppm OTO, BEI, A3	
· Ingre	edients with biological limit values:	
1330	-20-7 xylene	
	1.5 g/g creatinine Medium: urine	
	Time: end of shift	
	Parameter: Methylhippuric acids	
		(Contd. on page



Page 7/15

(Contd. of page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

Trade name: 894 BASECOAT SILVER DOLLAR COARSE

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine Medium: urine Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8)

LIS



Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

Trade name: 894 BASECOAT SILVER DOLLAR COARSE

· Eye protection:

Tightly sealed goggles

9 Physical and chemical properties

General Information	
Appearance:	
Form:	Liquid
Color:	Silver grey
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124 °C (255.2 °F)
Flash point:	25 °C (77 °F)
Flammability:	Flammable.
Auto igniting:	370 °C (698 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
Density at 20 °C (68 °F):	0.954 g/cm³ (7.96113 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.

Page 8/15

(Contd. of page 7)

US



Page 9/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

Trade name: 894 BASECOAT SILVER DOLLAR COARSE

Salubility in / Misaibility with	(Contd. of	page
 Solubility in / Miscibility with Water: 	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/	water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	75.6 %	
Coating VOC content:	75.60 %	
-	721.2 g/l / 6.02 lb/gal	
Material VOC content:	721.2 g/l / 6.02 lb/gal	
Solids content:	24.4 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

1 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	13,100 mg/kg (rat) >5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

· Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.

(Contd. on page 10)

US



Page 10/15

(Contd. of page 9)

3

2B

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

Trade name: 894 BASECOAT SILVER DOLLAR COARSE

· Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1330-20-7 xylene

100-41-4 ethylbenzene

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 11)

US

GENERAL

Page 11/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

Trade name: 894 BASECOAT SILVER DOLLAR COARSE

(Contd. of page 10)

Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

· UN-Number · DOT, ADR, IMDG, IATA	UN1263	
· UN proper shipping name · DOT · ADR · IMDG, IATA	Paint 1263 PAINT PAINT	
Transport hazard class(es) DOT	NOT APPLICABLE	
· Class · Label	6.1 Toxic substances 3	
· ADR, IMDG, IATA	3 Flammable liquids	
· Label	3	
· Packing group · DOT, ADR, IMDG, IATA	<i>III</i>	
 Environmental hazards: Marine pollutant: 	No	
 Special precautions for user EMS Number: Stowage Category 	Warning: Flammable liquids F-E, <u>S-E</u> A	
· Transport in bulk according to Annex	(II of	



Page 12/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

Trade name: 894 BASECOAT SILVER DOLLAR COARSE

	(Contd. of page
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
ADR	
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

None of the	e ingredients is listed.	
Section 31	3 (Specific toxic chemical listings):	
1330-20-7	xylene	
100-41-4	ethylbenzene	
71-36-3	butan-1-ol	
95-63-6	1,2,4-trimethylbenzene	
7664-38-2	phosphoric acid	
TSCA (To	kic Substances Control Act):	
123-86-4	n-butyl acetate	ACTIV
1330-20-7	xylene	ACTIV
100-41-4	ethylbenzene	ACTIV
71-36-3	butan-1-ol	ACTIV
107-98-2	1-methoxy-2-propanol	ACTIV
05 62 6	1,2,4-trimethylbenzene	ACTIV



Page 13/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

Trade name: 894 BASECOAT SILVER DOLLAR COARSE

	(Contd. of page 1
108-65-6 2-methoxy-1-methyle	-
7664-38-2 phosphoric acid	ACTIVE
· Hazardous Air Pollutants	
1330-20-7 xylene	
100-41-4 ethylbenzene	
Proposition 65	
· Chemicals known to cause car	icer:
100-41-4 ethylbenzene	
· Chemicals known to cause rep	roductive toxicity for females:
None of the ingredients is listed.	
· Chemicals known to cause rep	roductive toxicity for males:
None of the ingredients is listed.	
· Chemicals known to cause dev	elopmental toxicity:
None of the ingredients is listed.	
· Carcinogenic categories	
· EPA (Environmental Protection	n Agency)
1330-20-7 xylene	
100-41-4 ethylbenzene	Ĺ
71-36-3 butan-1-ol	Ĺ
95-63-6 1,2,4-trimethylbenzer	ne li
TLV (Threshold Limit Value)	`
1330-20-7 xylene	A
100-41-4 ethylbenzene	A
· NIOSH-Ca (National Institute fo	or Occupational Safety and Health)
None of the ingredients is listed.	

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

• Hazard-determining components of labeling: n-butyl acetate

(Contd. on page 14)

US



Page 14/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

Trade name: 894 BASECOAT SILVER DOLLAR COARSE

	(Contd. of page 1
ethylbenzene	
Naphtha (petroleum), hydrodesulfurized heavy	
Hazard statements	
Flammable liquid and vapor.	
Causes skin irritation.	
Suspected of causing cancer.	
May cause drowsiness or dizziness.	
Causes damage to the central nervous system through prolonged	
damage to the hearing organs through prolonged or repeated exposu	ure.
Precautionary statements	
Obtain special instructions before use.	· · · ·
Do not handle until all safety precautions have been read and unders	
Keep away from heat/sparks/open flames/hot surfaces No smoking	<i>)</i> .
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Do not eat, drink or smoke when using this product.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protec	
If on skin (or hair): Take off immediately all contaminated clothing. Ri	
IF INHALED: Remove person to fresh air and keep comfortable for b	reathing.
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Specific treatment (see on this label).	
Get medical advice/attention if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/natio	nal/international regulations. not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

· Contact: N/A

· Date of preparation / last revision 10/23/2024 / 1.1

(Contd. on page 15)

US



Page 15/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/23/2024

Reviewed on 07/30/2024

Trade name: 894 BASECOAT SILVER DOLLAR COARSE

(Contd. of page 14) Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 Skin Irritation 2: Skin corrosion/irritation - Category 2 Carcinogenicity 2: Carcinogenicity – Category 2 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3 Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) – Category 1 • * Data compared to the previous version altered. US