

Page 1/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

1 Identification

· Product identifier

- · Trade name: 724C BASECOAT GOLDEN GREEN
- · Article number: 724C
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet

• *Manufacturer/Supplier:* General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· Classification of the substance or mixture GHS02 Flame Flammable Liquids 3 H226 Flammable liquid and vapor. GHS08 Health hazard Carcinogenicity 2 H351 Suspected of causing cancer. GHS07 Skin Irritation 2 H315 Causes skin irritation. Eye Irritation 2A H319 Causes serious eye irritation. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness. · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2) US



acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Page 2/15

Trade name: 724C BASECOAT GOLDEN GREEN

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 GHS08 Signal word Warning · Hazard-determining components of labeling: 4-chloro-alpha, alpha, alpha-trifluorotoluene methyl acetate n-butyl acetate ethylbenzene · Hazard statements Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness. Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. (Contd. on page 3)

- US




acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Page 3/15

Trade name: 724C BASECOAT GOLDEN GREEN



· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

components:	
4-chloro-alpha,alpha,alpha-trifluorotoluene	>25- <i>≤</i> 50%
methyl acetate	>25- <i>≤</i> 50%
n-butyl acetate	>2.5- <i>≤</i> 10%
Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%
xylene	>2.5- <i>≤</i> 10%
ethyl 3-ethoxypropionate	<i>≤</i> 2.5%
ethylbenzene	<i>≤</i> 2.5%
	4-chloro-alpha,alpha,alpha-trifluorotoluene methyl acetate n-butyl acetate Solvent naphtha (petroleum), light arom. xylene ethyl 3-ethoxypropionate

4 First-aid measures

· Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

• After inhalation: In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 4)



acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 724C BASECOAT GOLDEN GREEN

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

<u>5 Fire</u>-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

250 ppm
5 ppm
130 ppm
1.6 ppm
33 ppm
100 ppm
50 ppm
60 ppm
(Contd. on page 5

(Contd. of page 3)

Page 4/15



Page 5/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 724C BASECOAT GOLDEN GREEN

70657-70-4	2-methoxypropyl acetate	(Contd. of page) 50 ppm
PAC-2:		
79-20-9	methyl acetate	1,700 ppm
123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
763-69-9	ethyl 3-ethoxypropionate	18 ppm
100-41-4	ethylbenzene	1100* ppm
107-98-2	1-methoxy-2-propanol	160 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
111-76-2	2-butoxyethanol	120 ppm
70657-70-4	2-methoxypropyl acetate	1,000 ppm
PAC-3:		
79-20-9	methyl acetate	10000* ppm
123-86-4	n-butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
763-69-9	ethyl 3-ethoxypropionate	110 ppm
100-41-4	ethylbenzene	1800* ppm
107-98-2	1-methoxy-2-propanol	660 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
111-76-2	2-butoxyethanol	700 ppm
70657-70-4	2-methoxypropyl acetate	5,000 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 6)

US



Page 6/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 724C BASECOAT GOLDEN GREEN

· Storage class: 3

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

79-20	0-9 methyl acetate	
PEL	Long-term value: 610 mg/m³, 200 ppm	
REL	Short-term value: 760 mg/m³, 250 ppm Long-term value: 610 mg/m³, 200 ppm	
TLV	Short-term value: 250 ppm Long-term value: 200 ppm	
123-8	86-4 n-butyl acetate	
PEL	Long-term value: 710 mg/m³, 150 ppm	
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm	
TLV	Short-term value: 150 ppm Long-term value: 50 ppm	
1330	-20-7 xylene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Long-term value: 20 ppm BEI, A4	
100-4	41-4 ethylbenzene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
REL	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Long-term value: 20 ppm OTO, BEI, A3	
	(Contd. o	n page

(Contd. of page 5)



Page 7/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 724C BASECOAT GOLDEN GREEN

	(Contd. of page 6)
-	redients with biological limit values:
	0-20-7 xylene
BEI	1.5 g/g creatinine Medium: urine
	Time: end of shift Parameter: Methylhippuric acids
100	-41-4 ethylbenzene
	0.15 g/g creatinine
	Medium: urine
	Time: end of shift at end of workweek
	Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)
Add	<i>litional information:</i> The lists that were valid during the creation were used as basis.
	nediately remove all soiled and contaminated clothing.
Stor Avc Bre In c exp	sh hands before breaks and at the end of work. re protective clothing separately. id contact with the eyes and skin. athing equipment: ase of brief exposure or low pollution use respiratory filter device. In case of intensive or longe osure use respiratory protective device that is independent of circulating air. tection of hands:
Stor Avc Bre In c exp	sh hands before breaks and at the end of work. re protective clothing separately. id contact with the eyes and skin. athing equipment: ase of brief exposure or low pollution use respiratory filter device. In case of intensive or longer osure use respiratory protective device that is independent of circulating air.
Stol Avc Bre In c exp Pro The Due pre	sh hands before breaks and at the end of work. re protective clothing separately. id contact with the eyes and skin. athing equipment: ase of brief exposure or low pollution use respiratory filter device. In case of intensive or longer osure use respiratory protective device that is independent of circulating air. tection of hands: Protective gloves glove material has to be impermeable and resistant to the product/ the substance/ the preparation. to missing tests no recommendation to the glove material can be given for the product/ the paration/ the chemical mixture.
Stol Avc Bre In c exp • Pro The Due pre Sela deg	sh hands before breaks and at the end of work. re protective clothing separately. id contact with the eyes and skin. athing equipment: ase of brief exposure or low pollution use respiratory filter device. In case of intensive or longer osure use respiratory protective device that is independent of circulating air. tection of hands: Protective gloves glove material has to be impermeable and resistant to the product/ the substance/ the preparation. te to missing tests no recommendation to the glove material can be given for the product/ the

be checked prior to the application. • Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8) - US



Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 724C BASECOAT GOLDEN GREEN

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

General Information	
Appearance:	
Form:	Liquid
Color:	Green
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	57 °C (134.6 °F)
Flash point:	27 °C (80.6 °F)
Flammability:	Flammable.
Auto igniting:	455 °C (851 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive ail vapor mixtures are possible.
Explosion limits:	
Lower:	3.1 Vol %
Upper:	16 Vol %
Vapor pressure at 20 °C (68 °F):	220 hPa (165 mm Hg)
Density at 20 °C (68 °F):	1.12 g/cm³ (9.3464 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.

Page 8/15

(Contd. of page 7)



Page 9/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 724C BASECOAT GOLDEN GREEN

	(Contd	of page
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/	water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	71.9 %	
Coating VOC content:	16.33 %	
-	417.5 g/l / 3.48 lb/gal	
Material VOC content:	182.9 g/l / 1.53 lb/gal	
Solids content:	28.0 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

1 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

(Contd. on page 10)

US



Page 10/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 724C BASECOAT GOLDEN GREEN

(Contd. of page 9)

2B

2B 3

3

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

1330-20-7 xylene

100-41-4 ethylbenzene

111-76-2 2-butoxyethanol

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:

• General notes: Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 11)

acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 724C BASECOAT GOLDEN GREEN

(Contd. of page 10)

Page 11/15

Uncleaned packagings:
Recommendation: Disposal must be made according to official regulations.

· UN-Number · DOT, ADR, IMDG, IATA	UN1263	
· UN proper shipping name · DOT · ADR	Paint 1263 PAINT	
· IMDG, IATA · Transport hazard class(es)	PAINT NOT APPLICABLE	
· DOT		
· Class · Label	3 Flammable liquids 3	
· Class · Label	3 Flammable liquids 3	
· Packing group · DOT, ADR, IMDG, IATA		
• Environmental hazards: • Marine pollutant:	No	
Special precautions for user EMS Number: Stowage Category	Warning: Flammable liquids F-E, <u>S-E</u> A	
· Transport in bulk according to Annex	c II of	



Г



Page 12/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 724C BASECOAT GOLDEN GREEN

	(Contd. of page
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
ADR	
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
Excepted quantities (ÉQ)	Code: E1
,	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

None of th	ne ingredients is listed.	
Section 3	13 (Specific toxic chemical listings):	
1330-20-7	' xylene	
100-41-4	t ethylbenzene	
111-76-2	2 2-butoxyethanol	
TSCA (To	exic Substances Control Act):	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	ACTIVE
79-20-9	methyl acetate	ACTIVE
9004-36-8	cellulose acetate butyrate	ACTIVE
123-86-4	1 n-butyl acetate	ACTIVE
1330-20-7	' xylene	ACTIVE
763-69-9	ethyl 3-ethoxypropionate	ACTIVE
100-41-4	t ethylbenzene	ACTIVE
	2 1-methoxy-2-propanol	ACTIVI



Page 13/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 724C BASECOAT GOLDEN GREEN

108-65-6	2-methoxy-1-methylethyl acetate	(Contd. of page 1
	2 2-butoxyethanol	ACTIV
· Hazardou	is Air Pollutants	I
1330-20-7	⁷ xylene	
100-41-4	t ethylbenzene	
· Propositi	on 65	
· Chemical	ls known to cause cancer:	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	
100-41-4	ethylbenzene	
· Chemical	Is known to cause reproductive toxicity for females:	
None of th	ne ingredients is listed.	
· Chemical	Is known to cause reproductive toxicity for males:	
None of th	ne ingredients is listed.	
· Chemical	ls known to cause developmental toxicity:	
None of th	ne ingredients is listed.	
Carcinog	enic categories	
-	vironmental Protection Agency)	
1330-20-7		1
100-41-4	t ethylbenzene	D
	2 2-butoxyethanol	N
· TLV (Thre	eshold Limit Value)	
1330-20-7		A
100-41-4	t ethylbenzene	A
	2 2-butoxyethanol	A
111-76-2		
	a (National Institute for Occupational Safety and Health)	

The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



· Signal word Warning

(Contd. on page 14)



Page 14/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 724C BASECOAT GOLDEN GREEN

	(Contd. of page 13
Н	lazard-determining components of labeling:
	-chloro-alpha,alpha,alpha-trifluorotoluene
n	nethyl acetate
n	-butyl acetate
е	thylbenzene
H	lazard statements
F	lammable liquid and vapor.
С	Causes skin irritation.
С	Causes serious eye irritation.
S	Suspected of causing cancer.
N	lay cause drowsiness or dizziness.
P	Precautionary statements
С	Obtain special instructions before use.
D	o not handle until all safety precautions have been read and understood.
K	eep away from heat/sparks/open flames/hot surfaces No smoking.
G	Fround/bond container and receiving equipment.
ι	lse explosion-proof electrical/ventilating/lighting/equipment.
ι	lse only non-sparking tools.
T	ake precautionary measures against static discharge.
	void breathing dust/fume/gas/mist/vapors/spray
V	Vash thoroughly after handling.
	lse only outdoors or in a well-ventilated area.
	Vear protective gloves/protective clothing/eye protection/face protection.
	on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	- INHALED: Remove person to fresh air and keep comfortable for breathing.
	in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and eas
	o do. Continue rinsing.
	exposed or concerned: Get medical advice/attention.
	Call a poison center/doctor if you feel unwell.
	pecific treatment (see on this label).
	ake off contaminated clothing and wash it before reuse.
	skin irritation occurs: Get medical advice/attention.
	eye irritation persists: Get medical advice/attention.
	n case of fire: Use CO2, powder or water spray to extinguish.
	tore in a well-ventilated place. Keep container tightly closed.
	tore in a well-ventilated place. Keep cool.
	tore locked up.
	Dispose of contents/container in accordance with local/regional/national/international regulations.
С	chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 15)



Page 15/15

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

Trade name: 724C BASECOAT GOLDEN GREEN

(Contd. of page 14)

US

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. • **Department issuing SDS:** Product safety department

- · Contact: N/A
- · Date of preparation / last revision 10/22/2024 / 1.1

 Abbreviations and acronvms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, ÉU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 3: Flammable liquids – Category 3 Skin Irritation 2: Skin corrosion/irritation - Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Carcinogenicity 2: Carcinogenicity – Category 2 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3 * Data compared to the previous version altered.