

Page 1/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024

Reviewed on 07/29/2024

1 Identification

- · Product identifier
- · Trade name: 775C BASECOAT PEARL FINE RUSSET
- · Article number: 775C
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: General Paint Co. S.A.L.

P.O. Box 7623

Beirut

LEBANON

info@generalpaint.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer.

Specific Target Organ Toxicity - Repeated Exposure H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)



Page 2/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 775C BASECOAT PEARL FINE RUSSET

(Contd. of page 1)

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

4-chloro-alpha,alpha,alpha-trifluorotoluene methyl acetate ethylbenzene

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed.

(Contd. on page 3)



Page 3/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 775C BASECOAT PEARL FINE RUSSET

(Contd. of page 2)

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 3

Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

_	· Dangerous components:		
79-20-9	methyl acetate	>25- <i>≤</i> 50%	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	>25- <i>≤</i> 50%	
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%	
1330-20-7	xylene	>2.5- <i>≤</i> 10%	
763-69-9	ethyl 3-ethoxypropionate	>2.5- <i>≤</i> 10%	
100-41-4	ethylbenzene	<i>≤</i> 2.5%	

4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation: In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 4)



Page 4/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 775C BASECOAT PEARL FINE RUSSET

(Contd. of page 3)

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.


See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

	totion circona for circonicalo	
· PAC-1:		
79-20-9	methyl acetate	250 ppm
1330-20-7	xylene	130 ppm
763-69-9	ethyl 3-ethoxypropionate	1.6 ppm
100-41-4	ethylbenzene	33 ppm
	(Co	ntd. on page 5)

- US



Page 5/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 775C BASECOAT PEARL FINE RUSSET

		(Con	td. of page
107-98-2	1-methoxy-2-propanol	(001)	100 ppm
	n-butyl acetate		5 ppm
108-65-6	2-methoxy-1-methylethyl acetate		50 ppm
	phosphoric acid	• • • • • • • • • • • • • • • • • • •	3 mg/m³
70657-70-4	2-methoxypropyl acetate	,	50 ppm
57-55-6	Propylene glycol	,	30 mg/m
78-83-1	butanol		150 ppm
· PAC-2:			
79-20-9	methyl acetate	1,7	00 ppm
1330-20-7	xylene)* ppm
763-69-9	ethyl 3-ethoxypropionate	18	ррт
100-41-4	ethylbenzene	110	00* ppm
107-98-2	1-methoxy-2-propanol	160) ррт
123-86-4	n-butyl acetate	200) ррт
108-65-6	2-methoxy-1-methylethyl acetate	1,0	00 ppm
7664-38-2	phosphoric acid	30	mg/m³
	2-methoxypropyl acetate	1,0	00 ppm
<i>57-55-</i> 6	Propylene glycol		00 mg/m ⁻
78-83-1	butanol	1,3	00 ppm
· PAC-3:			
79-20-9	methyl acetate	100	000* ppm
1330-20-7	xylene	250	00* ppm
763-69-9	ethyl 3-ethoxypropionate	110) ррт
100-41-4	ethylbenzene	180	00* ppm
107-98-2	1-methoxy-2-propanol	660) ррт
123-86-4	n-butyl acetate	300	00* ppm
	2-methoxy-1-methylethyl acetate	• • • • • • • • • • • • • • • • • • •	00* ppm
	phosphoric acid	• • • • • • • • • • • • • • • • • • •) mg/m³
	2-methoxypropyl acetate		00 ppm
57-55-6	Propylene glycol		00 mg/m ³
78-83-1	butanol	800	00* ppm

(Contd. on page 6)



Page 6/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 775C BASECOAT PEARL FINE RUSSET

(Contd. of page 5)

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At th	is time, the other constituents have no known exposure limits.
79-2	0-9 methyl acetate
PEL	Long-term value: 610 mg/m³, 200 ppm
REL	Short-term value: 760 mg/m³, 250 ppm Long-term value: 610 mg/m³, 200 ppm
TLV	Short-term value: 250 ppm Long-term value: 200 ppm
1330	-20-7 xylene
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm

(Contd. on page 7)



Page 7/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 775C BASECOAT PEARL FINE RUSSET

(Contd. of page 6)

TLV Long-term value: 20 ppm

BEI. A4

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm TLV Long-term value: 20 ppm

OTO, BEI, A3

· Ingredients with biological limit values:

1330-20-7 xylene

BEI 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 8)



Page 8/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 775C BASECOAT PEARL FINE RUSSET

(Contd. of page 7)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

. Intormation	on bacic	nhveical	and chemical	Inronortice
· IIIIOI IIIauoii	UII Dasic	viivsicai	anu chenina	บบบบยายยอ

· General Information

· Appearance:

Upper:

Form:	Liquid
Color:	Silver grey
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 57°C (134.6°F)
· Flash point:	-10 °C (14 °F)
· Flammability:	Highly flammable.
· Auto igniting:	455 °C (851 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits: Lower:	3.1 Vol %

16 Vol %

(Contd. on page 9)



Page 9/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 775C BASECOAT PEARL FINE RUSSET

		(Contd. of page
· Vapor pressure at 20 °C (68 °F):	220 hPa (165 mm Hg)	
· Density at 20 °C (68 °F):	1.115 g/cm³ (9.30468 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wat	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	73.6 %	
Coating VOC content:	14.78 %	
· ·	417.1 g/l / 3.48 lb/gal	
Material VOC content:	164.8 g/l / 1.38 lb/gal	
Solids content:	26.4 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.

(Contd. on page 10)



Page 10/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 775C BASECOAT PEARL FINE RUSSET

(Contd. of page 9)

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

• a. ceg	yomo catogones	
· IARC (Int	ternational Agency for Research on Cancer)	
98-56-6	6 4-chloro-alpha,alpha,alpha-trifluorotoluene	2B
1330-20-7	7 xylene	3
100-41-4	4 ethylbenzene	2B
· NTP (Nat	tional Toxicology Program)	
None of t	he ingredients is listed.	
· OSHA-Ca	a (Occupational Safety & Health Administration)	
None of ti	he ingredients is listed.	

12 Ecological information

- Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 11)



Page 11/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 775C BASECOAT PEARL FINE RUSSET

(Contd. of page 10)

- Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

Transport information	
· UN-Number · DOT, ADR, IMDG, IATA	UN1263
UN proper shipping name	
DOT	Paint
ADR IMDG, IATA	1263 PAINT PAINT
Transport hazard class(es)	NOT APPLICABLE
DOT	TVOT / IT ETO/IBEE
R MANUAL TOUR	
Class	3 Flammable liquids
Label	3
Class	3 Flammable liquids
Label	3
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
EMS Number:	F-E, <u>S-E</u>
Stowage Category	Α
Transport in bulk according to Ann	
MARPOL73/78 and the IBC Code	Not applicable.

(Contd. on page 12)





Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 775C BASECOAT PEARL FINE RUSSET

(Contd. of page 11) · Transport/Additional information: · DOT · Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L · ADR · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · IMDG · Limited quantities (LQ) 5L Excepted quantities (ÉQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · UN "Model Regulation": UN 1263 PAINT, 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

	55 (extremely hazardous substances):	
None of the	e ingredients is listed.	
· Section 31	3 (Specific toxic chemical listings):	
1330-20-7	xylene	
100-41-4	ethylbenzene	
7664-38-2	phosphoric acid	
· TSCA (To	ric Substances Control Act):	
79-20-9	methyl acetate	ACTIVE
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	ACTIVE
9004-36-8	cellulose acetate butyrate	ACTIVE
1330-20-7	xylene	ACTIVE
763-69-9	ethyl 3-ethoxypropionate	ACTIVE
100-41-4	ethylbenzene	ACTIVE
107-98-2	1-methoxy-2-propanol	ACTIVE
123-86-4	n-butyl acetate	ACTIVE
		(Contd. on page 13



Page 13/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 775C BASECOAT PEARL FINE RUSSET

100.05.0	O market and market darket a particle	(Contd. of pag
	2-methoxy-1-methylethyl acetate	
	phosphoric acid	ACTI
	Propylene glycol	ACTI
78-83-1	butanol	ACTI
· Hazardou	s Air Pollutants	
1330-20-7	xylene	
100-41-4	ethylbenzene	
Proposition		
Chemical	s known to cause cancer:	
	4-chloro-alpha,alpha,alpha-trifluorotoluene	
100-41-4	ethylbenzene	
Chemical	s known to cause reproductive toxicity for females:	
None of th	e ingredients is listed.	
Chemical	s known to cause reproductive toxicity for males:	
None of th	e ingredients is listed.	
Chemical	s known to cause developmental toxicity:	
None of th	e ingredients is listed.	
Carcinoge	enic categories	
· EPA (Env	ronmental Protection Agency)	
1330-20-7	xylene	
100-41-4	ethylbenzene	
· TLV (Thre	shold Limit Value)	
1330-20-7		
100-41-4	ethylbenzene	
NIOSH-Ca	(National Institute for Occupational Safety and Health)	
None of th	e ingredients is listed.	

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

(Contd. on page 14)



Page 14/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 775C BASECOAT PEARL FINE RUSSET

(Contd. of page 13)

· Hazard-determining components of labeling:

4-chloro-alpha,alpha,alpha-trifluorotoluene methyl acetate

ethylbenzene

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eve irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

US



Page 15/15

Safety Data Sheet acc. to OSHA HCS

Printing date 10/22/2024 Reviewed on 07/29/2024

Trade name: 775C BASECOAT PEARL FINE RUSSET

(Contd. of page 14)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 10/22/2024 / 1.0
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids - Category 2

Skin Irritation 2: Skin corrosion/irritation - Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2

* Data compared to the previous version altered.